STOCKPILE SAFETY PLAN

Company Name	Mine Name or Number
Date	Mine Index Number

Pursuant to 4 VAC 25-125-30 paragraphs C and D of the Regulations Governing Coal Stockpiles and Bulk Storage and Handling Facilities the following plan will be implemented and followed:

- 1) Methods for determining that no miners or equipment or in the affected area before starting stockpile underlying feeders:
 - a) A check-in and check-out system will be established. Anyone going onto or off the stockpile must check in or check-out. Before starting the feeders, operators will examine the check board. The feeders will not be started if someone is checked in.
 - b) Operators will visually examine the stockpile before starting feeders.
 - c) An announcement will be made over the two-way radio system one minute prior to starting feeders and again immediately prior.
- 2) Method for determining the expected draw hole size in correlation to the stockpile size.
 - a) Acceptable engineering calculations for the material in the stockpile will be used to calculate draw hole size.
 - b) The maximum draw hole size will be determined from the angle of draw of the material and other pertinent variables.
 - c) A chart will be maintained at the site showing expected draw hole size including variables such as height of material, moisture content, etc.
- 3) Safe procedures for breaking through bridged cavities.
 - a) Breaking through bridged cavities will be performed under the direct supervision of a certified foreman.
 - b) Feeders will be shut off, locked out, and tagged.
 - c) The stockpile will be worked with equipment from the determined bottom edge of the bridge upward until the bridge collapses.
 - d) Care will be taken to avoid creating hazardous slopes that could collapse.
- 4) Procedures for safe recovery of personnel should a piece of equipment become entrapped:

- a) Shut off feeders. Lock out and tag all electrical power to the feeders.
- b) Attempt to locate and establish communications with the entrapped person. Continue efforts throughout the extraction effort.
- c) Contact emergency personnel including designated certified person. Relay appropriate information.
- d) Coordinate equipment designated for such an emergency. A list with contact information will be maintained at the site.
- e) Contact MSHA and DM. Relay appropriate information.
- f) Extraction procedures:
 - i) Attempt to locate entrapped equipment as close as possible.
 - ii) Begin extraction efforts once equipment is in place and instructions have been received from a certified person.
 - iii) Remove material from the area surrounding the entrapment.
 - iv) Keep the area as level as possible. Do not create any hazardous slopes that could collapse.
- 5) Procedures for travel by foot travel during non-emergencies:
 - a) All foot travel will be under the direct supervision of a certified foreman.
 - b) Feeders will be de-energized, locked out and tagged.
 - c) Miners traveling by foot over the stockpile will be secured with a safety line.
- 6) Procedures for compliance:
 - a) This plan will be reviewed with all new personnel and with all personnel during annual retraining and during monthly safety talks.
 - b) Appropriate signs will be made and posted at pertinent locations to remind employees of procedures.

All other requirements of 4 VAC 25-125 will be complied with.

_	
	Company Official