



COMMONWEALTH OF VIRGINIA  
*Virginia Department of Energy*  
 Division of Mined Land Repurposing

NPDES Permit Number: 0081576  
 Associated CSMO Permit Number: 1601576  
 Permit Application Number: 1011619

Permit Original Issue Date: 9/27/1996  
 Application Approval Date: 11/18/2024  
 Expiration Date: 9/27/2026

**AUTHORIZATION TO DISCHARGE UNDER THE  
 VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM  
 AND  
 THE VIRGINIA STATE WATER CONTROL LAW**

Pursuant to Authority under Section 45.2-1029 of the Code of Virginia, as amended, and the Virginia Pollutant Discharge Elimination System (VPDES) Regulation, Part X - Delegation of Authority to the Department of Mines, Minerals and Energy for Coal Surface Mining Operations (9VAC25-31-940), the following owner is authorized to discharge from the facility listed below in compliance with the provisions of the Clean Water Act as amended and pursuant to the State Water Control Law and regulations adopted pursuant thereto and in accordance with the effluent limitations, monitoring requirements, and other conditions set forth in Sections A, B, C, and D of this permit and the plans and requirements found in joint CSMO/NPDES permit number 1601576/0081576 and any and all subsequent approved permitting actions. For the purpose of this permit, NPDES and VPDES permits are synonymous.

Owner: RED RIVER COAL COMPANY, INC.  
 Facility Name: BLACK CREEK SURFACE MINE  
 County: WISE  
 Facility Location: 0.3 MILES FROM BLACKWOOD/JOSEPHINE/LAUREL GROVE

The owner is authorized to discharge to the following receiving streams:

Stream Name	Stream Basin	Stream Subbasin	Stream Tier
BLACK CREEK	TENNESSEE	POWELL-POWELL RIVER DORCHESTER	Tier I
POWELL RIVER	TENNESSEE	POWELL RIVER	Tier I

\_\_\_\_\_  
 Director, Division of Mined Land Repurposing

\_\_\_\_\_  
 Date

### Permit Contents

The complete joint CSMO/NPDES permit consists of the following:

- I. The approved CSMO/NPDES Permit Application, and any and all subsequent approved permit revisions, renewals, midterms, anniversary reports, completion reports, and DMLR administrative actions.
- II. The CSMO/NPDES Permit Document, including
  - Permit Signature Page
  - Section A – Effluent Limitations and Monitoring Requirements
  - Section B – Schedule of Compliance (if applicable)
  - Section C – Standard Terms and Conditions
  - Section D – Other Requirements

### Facility Information

**Permittee Name:** RED RIVER COAL COMPANY, INC.  
**Address:** P. O. BOX 668  
**City:** NORTON **State:** VA **Zip:** 24273  
**Facility:** BLACK CREEK SURFACE MINE  
**Total permit acres:** 1331.78, WISE

### Application Information:

**Application Type:** PLANS REVISION

**Application Description:** To add Pond T/NPDES outfall 00T.

### NPDES Outfall Description:

NPDES outfalls associated with this permit result from the control of surface water runoff resulting from precipitation and/or groundwater discharges from coal mining activities associated with mining. Treatment facilities may include sedimentation structures, chemical treatment such as the addition of neutralizing agents or flocculants, or no treatment (in the case of direct discharge of underground mine drainage when treatment is not required to meet applicable effluent limitations). The following details describe the treatment facility or source associated with each approved outfall. Specific information regarding each outfall and facility is found in Section V and Section XII of the CSMO/NPDES permit.

Section A  
Permit Requirements

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

**Outfall G WEIR MPID 0003201**

<i>Parameter</i>	<i>Monthly Avg.</i>	<i>Maximum</i>	<i>Minimum</i>	<i>AEL Qualifying Event</i>	<i>Sample Rate/Interval</i>
Flow	NL GPM	NA	NA	NA	12/Quarter
pH	NL Std	9.0 Std	6.0 Std	NA	12/Quarter
Acidity	50 lbs/day	200 lbs/day	NA	NA	12/Quarter
Total Dissolved Solids	NL mg/l	NA	NA	NA	12/Quarter
Iron, Total	1.8 lbs/day	13.7 lbs/day	NA	NA	12/Quarter
Manganese, Total	3.8 lbs/day	11.0 lbs/day	NA	NA	12/Quarter
Sulfate	NL ml/l	NL	NA	NA	12/Quarter
Rep Chem	RMR	NA	NA	NA	1/Permit Term
Acute WET	RWETMR TUa	NA	NA	NA	4/Quarter – 1/Permit Term
Chronic WET	RWETMR TUc	NA	NA	NA	4/Quarter – 1/Permit Term

**Outfall H MPID 0002316**

<i>Parameter</i>	<i>Monthly Avg.</i>	<i>Maximum</i>	<i>Minimum</i>	<i>AEL Qualifying Event</i>	<i>Sample Rate/Interval</i>
Flow	NL GPM	NA	NA	NA	6/Quarter
pH	NL Std	9.0 Std	6.0 Std	NA	6/Quarter
Total Suspended Solids	35.0 mg/l	70.0 mg/l	NA	0.2 In	6/Quarter
Iron, Total	3.0 mg/l	6.0 mg/l	NA	0.2 In	6/Quarter
Manganese, Total	2.0 mg/l	4.0 mg/l	NA	0.2 In	6/Quarter
Settleable Solids	NL ml/l	0.5 ml/l	NA	NA	Optional AEL event

**Outfall IE MPID 0002314**

<i>Parameter</i>	<i>Monthly Avg.</i>	<i>Maximum</i>	<i>Minimum</i>	<i>AEL Qualifying Event</i>	<i>Sample Rate/Interval</i>
Flow	NL GPM	NA	NA	NA	3/Quarter
pH	NL Std	9.0 Std	6.0 Std	NA	3/Quarter
Total Dissolved Solids	NL mg/l	NA	NA	NA	3/Quarter
Settleable Solids	NL ml/l	0.5 ml/l	NA	NA	3/Quarter

**Outfall S MPID 0005150**

<i>Parameter</i>	<i>Monthly Avg.</i>	<i>Maximum</i>	<i>Minimum</i>	<i>AEL Qualifying Event</i>	<i>Sample Rate/Interval</i>
Flow	NL GPM	NA	NA	NA	6/Quarter
pH	NL Std	9.0 Std	6.0 Std	NA	6/Quarter
Total Suspended Solids	35.0 mg/l	70.0 mg/l	NA	0.2 In	6/Quarter
Total Dissolved Solids	NL mg/l	NA	NA	NA	6/Quarter
Iron, Total	3.0 mg/l	6.0 mg/l	NA	0.2 In	6/Quarter
Manganese, Total	2.0 mg/l	4.0 mg/l	NA	0.2 In	6/Quarter
Settleable Solids	NL ml/l	0.5 ml/l	NA	NA	Optional AEL event

**Outfall T MPID 0012749**

<i>Parameter</i>	<i>Monthly Avg.</i>	<i>Maximum</i>	<i>Minimum</i>	<i>AEL Qualifying Event</i>	<i>Sample Rate/Interval</i>
Flow	NL GPM	NA	NA	NA	6/Quarter
pH	NL Std	9.0 Std	6.0 Std	NA	6/Quarter
Total Suspended Solids	35.0 mg/l	70.0 mg/l	NA	0.2 In	6/Quarter
Total Dissolved Solids	NL mg/l	NA	NA	NA	6/Quarter
Iron, Total	3.0 mg/l	6.0 mg/l	NA	0.2 In	6/Quarter
Manganese, Total	2.0 mg/l	4.0 mg/l	NA	0.2 In	6/Quarter
Settleable Solids	NL ml/l	0.5 ml/l	NA	NA	Optional AEL event

A) The collection method is to be a grab sample for all measurements except for flow, which may be either measured or estimated.

B) Samples for parameters required at a rate of 6/Quarter shall be collected twice per calendar month, at least seven days apart. Samples for parameters required at a rate of 3/Quarter shall be collected once per calendar month, at least seven days apart.

C) Monthly Avg. is to be the arithmetic mean of all samples collected in a calendar month. Max is to be a daily maximum and min is to be daily minimum for all measured parameters except for pH, which is to be measured as an instantaneous maximum and instantaneous minimum. All limits are followed by the units in which they are to be measured.

D) NL indicates monitoring is required with no limitations (No Limit). NA indicates the parameter does not apply to the particular outfall (Not Applicable).

E) RMR stands for Representative Monitoring Required. RWETMR stands for Representative Whole Effluent Toxicity Monitoring Required.

F) The AEL Qualifying Event is the minimum rainfall event necessary for AELs (alternate effluent limitations) to apply to the specified parameter for the given outfall. The utilization of AELs is optional. Settleable solids analysis is required only if AELs are claimed.

G) TSS and TDS, when listed in an above table, are to be collected and reported at all times, even when an AEL is utilized.

H) For any outfall designated as commingled (surface runoff/underground mine drainage) with an AEL precipitation minimum equivalent to a 10Y/24H event, if the treatment structure(s) are not controlling any underground mine drainage and contain only surface runoff (other than refuse areas) then a 0.2 inch AEL minimum shall apply. Application of the AEL is subject to all other conditions of 40 CFR 434. The permittee is responsible for maintaining such records necessary to meet the burden of proof for the AEL, including the date that underground mine dewatering, either pumped or gravity, last occurred.

## B. OTHER REQUIREMENTS

The term Department refers to the Virginia Department of Energy

1. This permit shall be modified, or alternatively revoked and reissued, to comply with any applicable effluent standard, limitation or prohibition for a pollutant which is promulgated or approved under Section 307(a)(2) of the Clean Water Act, if the effluent standard, limitation, or prohibition so promulgated or approved:
  - a. Is more stringent than any effluent limitation on the pollutant already in the permit; or
  - b. Controls any pollutant not limited in the permit.
2. This permit shall be modified or alternatively revoked and reissued if any approved waste load allocation procedure, pursuant to Section 303(d) of the Clean Water Act, imposes waste load allocations, limits or conditions on the facility that are not consistent with the permit requirements.
3. This permit may be modified or alternatively revoked and reissued to incorporate appropriate limits in the event effluent monitoring indicates the need for any water quality-based limits.
4. The permittee shall notify the Department as soon as they know or have reason to believe:
  - a. That any activity has occurred or will occur which would result in the discharge, on a routine or frequent basis, of any toxic pollutant which is not limited in this permit, if that discharge will exceed the highest of the following notification levels:
    - (1) One hundred micrograms per liter;
    - (2) Two hundred micrograms per liter for acrolein and acrylonitrile; five hundred micrograms per liter for 2,4-dinitrophenol and for 2-methyl-4,6-dinitrophenol; and one milligram per liter for antimony;
    - (3) Five times the maximum concentration value reported for that pollutant in the permit application; or
    - (4) The level established by the Board.
  - b. That any activity has occurred or will occur which would result in any discharge, on a non-routine or infrequent basis, of a toxic pollutant which is not limited in this permit, if that discharge will exceed the highest of the following notification levels:
    - (1) Five hundred micrograms per liter;
    - (2) One milligram per liter for antimony;
    - (3) Ten times the maximum concentration value reported for that pollutant in the permit application; or
    - (4) The level established by the Board.
5. Any and all product, materials, industrial wastes, and/or other wastes resulting from the purchase, sale, mining, extraction, transport, preparation, and/or storage of raw or intermediate materials, final product, by-product or wastes, shall be handled, disposed of, and/or stored in such a manner and consistent with Best Management Practices, so as not to permit a discharge of such product, materials, industrial wastes, and/or other wastes to State waters, except as expressly authorized.
6. The permittee shall monitor the effluent that is representative of outfall(s) N/A for the substances noted in Part II, Section A.E.2, Table 1 according to the indicated analysis

number, quantification level, sample type and frequency. The outfalls listed above may be representative of a group of substantially similar outfalls on this mining operation.

Effluent characterization data was provided in Renewal Application 1011100 and 1011092. The effluent characterization requirement for Application 1011619 has been satisfied. Additional effluent characterization will be required if the permittee chooses to renew the permit for a subsequent permit term. Additional effluent characterization may also be required if the permit is revised or if a substantive change to the nature of the effluent occurs.

For new and proposed mining operations, the monitoring shall begin within six months of completion of construction of the first sedimentation basin serving any of each of these groups of substantially similar outfall locations, or as soon as a measurable discharge occurs. If the representative outfall is not constructed first or is not the first outfall of the group represented to discharge active mine drainage [Part II Section C NPDES Definitions, (B)], the first discharging outfall within a substantially similar group should be utilized. The sampled outfall will then serve as the representative outfall for this group unless otherwise determined by the Division. The permittee should send notification to the Division prior to sampling if the designated representative outfall is not utilized.

Sampling and analysis of the representative outfalls is also required at permit renewal.

The data shall be submitted with the discharge monitoring report for the final month of the calendar quarter in which the sampled discharge occurred. The data shall also be submitted with the materials required for permit reissuance.

Monitoring and analysis shall be conducted in accordance with 40 CFR Part 136 or alternative EPA approved methods. It is the responsibility of the permittee to ensure that proper QA/QC protocols are followed during the sample gathering and analytical procedures. The Department will use these data for making specific permit decisions in the future. This permit may be modified or, alternatively, revoked and reissued to incorporate limits for any of the substances listed in Part II, Section A.E.3, Table 1.

7. The permittee shall comply with the following reporting requirements for all Section A monitoring:

a. The quantification levels (QL) shall be less than or equal to the following concentrations:

<u>Effluent Parameter</u>	<u>Quantification Level</u>
TSS	1.0 mg/l
TDS	1.0 mg/l
Iron	1.0 mg/l
Manganese	1.0 mg/l
Selenium	2.5 µg/l

The QL is defined as the lowest concentration used to calibrate a measurement system in accordance with the procedures published for the method. It is the responsibility of the permittee to ensure that proper quality assurance and quality control (QA/QC) protocols are followed during the sampling and analytical

procedures. QA/QC information shall be documented to confirm that appropriate analytical procedures have been used and the required QLs have been attained with the required precision. The permittee shall use any method in accordance with Part II Section C of this permit. The permittee shall use a VELAP certified analytical laboratory for all submitted analyses.

- b. **Monthly Average** -- Compliance with the monthly average limitations and/or reporting requirements for the parameters listed in Part II Section A of this permit condition shall be determined as follows: All concentration data below the QL given in Part II Section B.7.a will be treated as zero. All concentration data equal to or above the QL used for the analysis should be treated as reported. An arithmetic average is to be calculated using all reported data for the month, including the defined zeros. This arithmetic average must be reported on the Discharge Monitoring Report (DMR). If all measured values are below the QL used for the analysis, then the arithmetic average is to be defaulted to  $\frac{1}{2}$  of the QL. If a quantified report is required on the DMR and the reported monthly average concentration is less than the QL, the monthly average is to be recorded as  $\frac{1}{2}$  of the QL value. If a quantified report is required on the DMR and the reported monthly average is greater than the QL, the actual reported data including defined zeroes is to be used along with flow data for each sample day to determine the daily averages. The monthly average is then to be reported as the arithmetic mean of the daily averages.

**Daily Maximum** -- Compliance with the daily maximum limitations and/or reporting requirements for the parameters listed in Part II Section A of this permit condition shall be determined as follows: All concentration data below the QL used for the analysis (QL must be less than or equal to the QL listed in a. above) shall be treated as zero. All concentration data equal to or above the QL used for the analysis (QL must be less than or equal to the QL listed in a. above) shall be treated as reported. An arithmetic mean shall be calculated using all reported data, including the defined zeros, collected within each day during the reporting month. The maximum value of these daily averages shall be reported on the DMR as the Daily Maximum. If all data are below the QL used for the analysis (QL must be less than or equal to the QL listed in Part II Section B.7.a), the maximum value of the daily averages shall be reported numerically as  $\frac{1}{2}$  of the QL. If a quantified measurement is required on the DMR and the reported daily maximum is less than the QL, the daily maximum for the measured parameter is to be reported as  $\frac{1}{2}$  of the given QL. In all other cases, the reported daily average concentrations (including the defined zeros) and corresponding daily flows are to be used in daily mean calculations.

**Single Datum** - Any single datum required shall be reported numerically as  $\frac{1}{2}$  of the QL if it is less than the QL used in the analysis (QL must be less than or equal to the QL listed in Part II Section A.B.7.a. above). Otherwise the numerical value shall be reported.

- c. **Significant Digits** -- The permittee shall report at least the same number of significant digits as the permit limit for a given parameter. Regardless of the rounding convention used by the permittee (i.e., 5 always rounding up or to the nearest even number), the permittee shall use the convention consistently, and shall ensure that consulting laboratories employed by the permittee use the same convention.





C. WHOLE EFFLUENT TOXICITY TESTING:

1. Acute Monitoring: Outfall(s) G

- a. The permittee shall monitor effluent that is representative of Outfall(s) (None) within 6 months of approval of this NPDES permit for acute toxicity tests until there are a minimum of 4 for each test required. The permittee shall perform these tests quarterly.

For new and proposed mining operations, the monitoring shall begin within six months of completion of construction of the first sedimentation basin serving any of each of these groups of substantially similar outfall locations, or as soon as a measurable discharge occurs. If the representative outfall is not constructed first or is not the first outfall of the group represented to discharge active mine drainage [Part II Section C NPDES Definitions, (B)], the first discharging outfall within a substantially similar group should be utilized. The sampled outfall will then serve as the representative outfall for this group unless otherwise determined by the Division. The permittee should send notification to the Division prior to sampling if the designated representative outfall is not utilized.

The acute tests to use are:

- 48 Hour Static Acute test with *Ceriodaphnia dubia* (EPA Method 2002)
- 48 Hour Static Acute test with *Pimephales promelas* (EPA Method 2000)

These acute tests are to be conducted using 5 geometric dilutions of effluent with a minimum of 4 replicates, with 5 organisms in each. The NOAEC (No Observed Adverse Effect Concentration), as determined by hypothesis testing, shall be reported on the DMR. The LC<sub>50</sub> should also be determined and noted on the submitted report. Tests in which control survival is less than 90% are not acceptable.

- b. The test dilutions should be able to determine compliance with the following endpoint:

$$\text{NOAEC} = 100\%$$

- c. The permittee shall submit the following information with the results of the toxicity tests:

- (1) An estimate of the total volume discharged and the duration of the discharge.
- (2) The time at which the discharge was initiated.
- (3) The time at which sampling was initiated.

- d. The permittee may provide additional samples to address data variability during the period of initial data generation. These data shall be reported and may be included in the evaluation of effluent toxicity. Test procedures and reporting shall be in accordance with the WET testing methods cited in 40 CFR 136.3.

- e. The assembled data will be evaluated for reasonable potential at the conclusion of the test period. The data may be evaluated sooner if such evaluation is requested by

the permittee or if toxicity has been demonstrated over the course of sampling. Should evaluation of the data indicate that a limit is needed, WET limits and associated compliance schedules will be imposed and the permittee may cease the toxicity tests outlined in Part II Section C.1.a.

- f. If evaluation of the assembled data results in the conclusion that no limit is needed, the permittee shall perform an acute WET test for each species of each representative outfall at permit renewal as defined on the reporting schedule contained in Part II Section C.3. All applicable data will be reevaluated for reasonable potential at the end of the permit term.
- g. The permit may be modified or revoked and reissued to include pollutant specific limits in lieu of a WET limit should it be demonstrated that toxicity is due to specific parameters. The pollutant specific limits must control the toxicity of the effluent.

2. Acute and Chronic Monitoring: Outfall(s) G

- a. The permittee shall monitor effluent that is representative of Outfall(s) (None) within 6 months of approval of this NPDES permit for acute and chronic toxicity tests until there are a minimum of 4 for each test required. The permittee shall perform these tests quarterly.

For new and proposed mining operations, the monitoring shall begin within six months of completion of construction of the first sedimentation basin serving any of each of these groups of substantially similar outfall locations, or as soon as a measurable discharge occurs. If the representative outfall is not constructed first or is not the first outfall of the group represented to discharge active mine drainage [Part II Section C NPDES Definitions, (B)], the first discharging outfall within a substantially similar group should be utilized. The sampled outfall will then serve as the representative outfall for this group unless otherwise determined by the Division. The permittee should send notification to the Division prior to sampling if the designated representative outfall is not utilized.

The acute tests to use are:

- 48 Hour Static Acute test with *Ceriodaphnia dubia* (EPA Method 2002)
- 48 Hour Static Acute test with *Pimephales promelas* (EPA Method 2000)

These acute tests are to be conducted using 5 geometric dilutions of effluent with a minimum of 4 replicates, with 5 organisms in each. The NOAEC (No Observed Adverse Effect Concentration), as determined by hypothesis testing, shall be reported on the DMR. The LC<sub>50</sub> should also be determined and noted on the submitted report. Tests in which control survival is less than 90% are not acceptable. The chronic tests to use are:

Chronic 3-Brood Survival and Reproduction Static Renewal Test with *Ceriodaphnia dubia* (EPA Method 1002)

Chronic 7-Day Survival and Growth Static Renewal Test with *Pimephales promelas* (EPA Method 1000)

These chronic tests shall be conducted in such a manner and at sufficient dilutions (minimum of five dilutions, derived geometrically) to determine the "No Observed Effect Concentration" (NOEC) for survival and reproduction or growth. Results which cannot be quantified (i.e., a "less than" NOEC value) are not acceptable, and a retest will have to be performed. A retest of a non-acceptable test must be performed within 30 days of the test it is replacing. Express the test NOEC as  $TU_c$  (Chronic Toxic Units), by dividing  $100/NOEC$  for DMR reporting. Report the  $LC_{50}$  at 48 hours and the  $IC_{25}$  with the NOEC's in the test report.

- b. The test dilutions should be able to determine compliance with the following endpoint:

Acute NOAEC = 100%  
Chronic NOEC of 69% equivalent to a  $TU_c$  of 1.44

- c. The permittee shall submit the following information with the results of the toxicity tests:

- (1). Estimate of the total volume discharged and the duration of the discharge.
- (2). Time at which the discharge was initiated.
- (3). Time at which sampling was initiated.

- d. The permittee may provide additional samples to address data variability during the period of initial data generation. These data shall be reported and may be included in the evaluation of effluent toxicity. Test procedures and reporting shall be in accordance with the WET testing methods cited in 40 CFR 136.3.

- e. The test data will be evaluated statistically for reasonable potential at the conclusion of the test period. The data may be evaluated sooner if requested by the permittee, or if toxicity has been noted. Should evaluation of the data indicate that a limit is needed, a WET limit and compliance schedule will be required and the toxicity tests of Part II Section C.2.a may be discontinued.

- f. If after evaluating the data, it is determined that no limit is needed, the permittee shall continue acute and chronic toxicity testing (both species) of each representative outfall at renewal, as on the reporting schedule contained in Part II Section C.3. All applicable data will be reevaluated for reasonable potential at the end of the permit term.

- g. The permit may be modified or revoked and reissued to include pollutant specific limits in lieu of a WET limit should it be demonstrated that toxicity is due to specific parameters. The pollutant specific limits must control the toxicity of the effluent.

3. Reporting Schedule:

The permittee shall report the results of the toxicity tests on the appropriate DMR or other methods prescribed by the Department and supply one copy of the toxicity test reports specified in this Whole Effluent Toxicity Program. This data is to be provided within 30 days following the end of the calendar quarter in which the analysis was completed.

D. EVALUATION OF TMDL COMPLIANCE:

To be consistent with the assumptions and requirements of the applicable Total Maximum Daily Load (TMDL) and any mining waste load allocations contained in the TMDL, the permittee shall implement best management practices (BMPs) as established in any compliance schedule included in the permit for this facility.

The BMPs and other requirements of the compliance schedule shall serve as water quality-based effluent limitations for this facility.

TMDL Reopener Clause

This permit is subject to a TMDL Reopener Clause as described in Part II Section D TMDL Special Conditions (a).

E. STREAM MONITORING CONDITIONS:

1. Biological surveys are to be completed once annually during the fall collection season to determine the benthic health of POWELL RIVER at locations PR1 and PR2 and BLACK CREEK at locations BC1, BC4, and BC3 as outlined in the joint CSMO/NPDES permit (Part I, Sections 8.3 and 21.2). DEQ's Virginia Stream Condition Index (VASCI) will be utilized to determine a score for each monitoring location. The Department may also consider applicable VASCI scores generated by DEQ. The stream habitat scores and chemical data will also be collected at these locations. All biologic sampling shall be done in accordance with applicable protocols as described below. Biological survey results will need to be submitted by March 1<sup>st</sup> of the next calendar year following the date the survey was conducted.

The benthic surveys shall be conducted annually each year in the fall season period determined by DEQ, avoiding to the maximum extent practicable times when the sample location is influenced by abnormal conditions, including drought and/or scouring flood. All biological surveys should be conducted as close to the anniversary date of the original surveys as possible. In addition, all biologic sampling shall be done in accordance with the Virginia Department of Wildlife Resources scientific collection permit and DEQ's Virginia Stream Condition Index (VASCI) protocol. The DEQ has developed the following procedure.

- Conduct benthic sampling using Virginia benthic protocols including time of year restrictions for sample collection.
  - Collect organisms, laboratory subsample to 200 +/- 10% (220-180) organisms in a gridded pan.
  - Identify organisms to genus level, excluding chironomids (midges) and any organisms which cannot be accurately identified to genus, which are instead identified to family level. All organisms, whether identified to genus or family level, are included in the count going forward.
  - Collapse data to family level
  - Statistically rarify data to 110 +/- 10% (99-121) organisms; computer subsampling programs available.
  - Calculate the VASCI score
  - Provide raw 200 +/- 10% (220-180) count genus-level data in electronic spreadsheet format.
2. The permittee shall conduct chemical surface water monitoring at instream locations BC1, BC3, BC4, PR1, and PR2 as described in Section 8.3 of the joint CSMO/NPDES permit and shown on the applicable map (Attachment 21.2.E). This monitoring is to be conducted concurrent with the biological surveys required under item Part II Section A.E.1. Fall chemical monitoring will need to be submitted by March 1<sup>st</sup> of the next calendar year following the fall collection date. The permittee has the option of conducting metals analyses for total metals only even though instream water quality standards are based on dissolved metal concentrations. If total metal analyses concentrations exceed instream standards, the permittee may collect dissolved metal samples for those metals exceeding instream standards to confirm whether or not the instream standard has been met. Otherwise the total metals concentration will be used to determine compliance with the instream standard.

3. The data provided to satisfy Part II Section A, at a minimum, will be evaluated upon each major modification and permit renewal to determine whether permit modifications are necessary. Should any of the data indicate that the discharges from this operation have the potential to cause or contribute to a violation of either a numeric or narrative water quality standard, additional pollutant specific limits or whole effluent toxicity limits shall be imposed.

**TABLE 1 - Parameters**

**Parameter**

Flow (gpm)  
Temperature (°c)  
pH (std units)  
TSS (mg/L)  
Specific Conductance (µS/cm)  
TDS (mg/L)  
Sulfates (mg/L)  
Bromide (mg/L)  
Chlorides (mg/L)  
Aluminum (mg/L)  
Iron (mg/L)  
Manganese (mg/L)  
Magnesium (mg/L)  
Total Acidity (mg/L)  
Total Alkalinity (mg/L CaCO<sub>3</sub>)  
Bicarbonate Alkalinity (mg/L)  
Carbonate Alkalinity (mg/L)  
Hardness (mg/L CaCO<sub>3</sub>)  
Total Zinc (µg /L)  
Total Antimony (µg /L)  
Total Arsenic (µg /L)  
Total Beryllium (µg /L)  
Total Cadmium (µg /L)  
Total Chromium (µg /L)  
Total Copper (µg /L)  
Total Lead (µg /L)  
Total Mercury (µg/L)  
Total Nickel (µg /L)  
Total Selenium (µg/L)  
Total Silver (µg /L)  
Total Thallium (µg /L)  
Total Barium (µg/L)  
Total Boron (µg/L)  
Total Cobalt (µg/L)  
Total Cyanide (µg/L)  
Total Phenols (µg/L)  
Nitrate (mg/L)  
Nitrite (mg/L)  
Dissolved Organic Carbon (mg/L)  
Hydrogen Sulfide (mg/L)<sup>1</sup>

---

<sup>1</sup> This parameter need only be analyzed for underground mine discharges.

**Section B**  
**Schedule of Compliance**

A schedule of compliance is not required.



**Section C**  
**Standard NPDES Permit Terms and Conditions**

The term Department refers to the Virginia Department of Mines, Minerals, and Energy.

A. Monitoring.

1. Samples and measurements taken as required by this permit shall be representative of the monitored activity.
2. Monitoring shall be conducted according to procedures approved under Title 40 Code of Federal Regulations Part 136 or alternative methods approved by the U.S. Environmental Protection Agency, unless other procedures have been specified in this permit.
3. The permittee shall periodically calibrate and perform maintenance procedures on all monitoring and analytical instrumentation at intervals that will ensure accuracy of measurements.

B. Records.

1. Records of monitoring information shall include:
  - a. The date, exact place, and time of sampling or measurements;
  - b. The individual(s) who performed the sampling or measurements;
  - c. The date(s) and time(s) analyses were performed;
  - d. The individual(s) who performed the analyses;
  - e. The analytical techniques or methods used; and
  - f. The results of such analyses.
2. The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of the sample, measurement, report or application, excluding records of monitoring information required by this permit related to sewage sludge use and disposal activities, which shall be retained for a period of at least five years. This period of retention shall be extended automatically during the course of any unresolved litigation regarding the regulated activity or regarding control standards applicable to the permittee, or as requested by the Department.

C. Reporting Monitoring Results.

1. The permittee shall submit the results of the monitoring required by this permit not later than 30 days following the quarter in which monitoring takes place, unless another reporting schedule is specified elsewhere in this permit. Monitoring results shall be submitted to:

Virginia Department of Energy  
Attn: DMLR Water Quality Section  
3405 Mountain Empire Rd  
Big Stone Gap, VA 24219

2. Monitoring results shall be reported on forms provided, approved or specified by the Department.

3. If the permittee monitors any pollutant specifically addressed by this permit more frequently than required by this permit using test procedures approved under Title 40 of the Code of Federal Regulations Part 136 or using other test procedures approved by the U.S. Environmental Protection Agency or using procedures specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or reporting format specified by the Department, including electronic submittal.
4. Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean unless otherwise specified in this permit.

D. Duty to Provide Information.

The permittee shall furnish to the Department, within a reasonable time, any information which the Department may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The Department may require the permittee to furnish, upon request, such plans, specifications, and other pertinent information as may be necessary to determine the effect of the wastes from his discharge on the quality of state waters, or such other information as may be necessary to accomplish the purposes of the State Water Control Law. The permittee shall also furnish to the Department upon request, copies of records required to be kept by this permit.

E. Compliance Schedule Reports.

Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.

F. Unauthorized Discharges.

Except in compliance with this permit, or another permit issued by the Department, it shall be unlawful for any person to:

1. Discharge into state waters sewage, industrial wastes, other wastes, or any noxious or deleterious substances; or
2. Otherwise alter the physical, chemical or biological properties of such state waters and make them detrimental to the public health, or to animal or aquatic life, or to the use of such waters for domestic or industrial consumption, or for recreation, or for other uses.

G. Reports of Unauthorized Discharges.

Any permittee who discharges or causes or allows a discharge of sewage, industrial waste, other wastes or any noxious or deleterious substance into or upon state waters in violation of Part II Section C (F); or who discharges or causes or allows a discharge that may reasonably be expected to enter state waters in violation of Part II Section C (F); shall notify the Department of the discharge immediately upon discovery of the discharge, but in no case later than 24 hours after said discovery. A written report of the unauthorized discharge shall be submitted to the Department, within five days of discovery of the discharge. The written report shall contain:

1. A description of the nature and location of the discharge;
2. The cause of the discharge;
3. The date on which the discharge occurred;

4. The length of time that the discharge continued;
5. The volume of the discharge;
6. If the discharge is continuing, how long it is expected to continue;
7. If the discharge is continuing, what the expected total volume of the discharge will be; and
8. Any steps planned or taken to reduce, eliminate and prevent a recurrence of the present discharge or any future discharges not authorized by this permit.

Discharges reportable to the Department under the immediate reporting requirements of other regulations are exempted from this requirement.

H. Reports of Unusual or Extraordinary Discharges.

If any unusual or extraordinary discharge including a bypass or upset should occur from a treatment works and the discharge enters or could be expected to enter state waters, the permittee shall promptly notify, in no case later than 24 hours, the Department by telephone after the discovery of the discharge. This notification shall provide all available details of the incident (details of any adverse effects on aquatic life and the known number of fish killed must also be reported to DEQ). The permittee shall reduce the report to writing and shall submit it to the Department within five days of discovery of the discharge in accordance with Section C.I.2. Unusual and extraordinary discharges include but are not limited to any discharge resulting from:

1. Unusual spillage of materials resulting directly or indirectly from processing operations;
2. Breakdown of processing or accessory equipment;
3. Failure or taking out of service some or all of the treatment works; and
4. Flooding or other acts of nature.

I. Reports of Noncompliance

The permittee shall report any noncompliance which may adversely affect state waters or may endanger public health.

1. An oral report shall be provided within 24 hours from the time the permittee becomes aware of the circumstances. The following shall be included as information which shall be reported within 24 hours under this paragraph:
  - a. Any unanticipated bypass; and
  - b. Any upset which causes a discharge to surface waters.
2. A written report shall be submitted within 5 days and shall contain:
  - a. A description of the noncompliance and its cause;
  - b. The period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and
  - c. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

The Department may waive the written report on a case-by-case basis for reports of noncompliance under Part II Section C.I. if the oral report has been received within 24 hours and no adverse impact on state waters has been reported.

3. The permittee shall report all instances of noncompliance not reported under Part II Section I.1 or Part II Section I.2, in writing, at the time the next monitoring reports are submitted. The reports shall contain the information listed in Part II Section I.2.

**NOTE: The immediate (within 24 hours) reports required in Part II Section C (G, H and I) may be made to the Department's Big Stone Gap Office Enforcement Section at (276) 523-8199 (voice). For emergencies the Virginia Department of Emergency Services maintains a 24 hour telephone service at 1-800-468-8892.**

J. Notice of Planned Changes.

1. The permittee shall give notice to the Department as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when:
  - a. The permittee plans alteration or addition to any building, structure, facility, or installation from which there is or may be a discharge of pollutants, the construction of which commenced:
    - (1) After promulgation of standards of performance under Section 306 of Clean Water Act which are applicable to such source; or
    - (2) After proposal of standards of performance in accordance with Section 306 of Clean Water Act which are applicable to such source, but only if the standards are promulgated in accordance with Section 306 within 120 days of their proposal;
  - b. The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants which are subject neither to effluent limitations nor to notification requirements specified elsewhere in this permit; or
  - c. The alteration or addition results in a significant change in sludge use or disposal practices, and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan.
2. The permittee shall give advance notice to the Department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.

K. Signatory Requirements.

1. Applications. All permit applications shall be signed as follows:
  - a. For a corporation: by a responsible corporate officer. For the purpose of this section, a responsible corporate officer means: (i) A president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy- or decision-making functions for the corporation, or (ii) the manager of one or more manufacturing, production, or operating facilities, provided the manager is authorized to make management decisions which govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements; and where

- authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures;
- b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively; or
  - c. For a municipality, state, federal, or other public agency: By either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a public agency includes: (i) The chief executive officer of the agency, or (ii) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency.
2. Reports, etc. All reports required by permits, and other information requested by the Department shall be signed by a person described in Part II Section C.K.1, or by a duly authorized representative of that person. A person is a duly authorized representative only if:
    - a. The authorization is made in writing by a person described in Part II Section C.K.1;
    - b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or any individual occupying a named position.); and
    - c. The written authorization is submitted to the Department.
  3. Changes to authorization. If an authorization under Part II Section C.K.2 is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part II Section C.K.2 shall be submitted to the Department prior to or together with any reports, or information to be signed by an authorized representative.
  4. Certification. Any person signing a document under Part II Section C.K.1 or 2 shall make the following certification:  
 "I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

L. Duty to Comply.

The permittee shall comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Coal Surface Mining Operation permit, State Water Control Law and the Clean Water Act, except that noncompliance with certain provisions of this permit may constitute a violation of the State Water Control Law but not the Clean Water Act. Permit noncompliance is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or denial of a permit renewal application.

The permittee shall comply with effluent standards or prohibitions established under Section 307(a) of the Clean Water Act for toxic pollutants and with standards for sewage sludge use or disposal established under Section 405(d) of the Clean Water Act within the time provided in the regulations

that establish these standards or prohibitions or standards for sewage sludge use or disposal, even if this permit has not yet been modified to incorporate the requirement.

M. Duty to Reapply.

If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee shall apply for and obtain a new permit. All permittees with a currently effective permit shall submit a new application at least 180 days before the expiration date of the existing permit, unless permission for a later date has been granted by the Department. The Department shall not grant permission for applications to be submitted later than the expiration date of the existing permit.

N. Effect of a Permit.

This permit does not convey any property rights in either real or personal property or any exclusive privileges, nor does it authorize any injury to private property or invasion of personal rights, or any infringement of federal, state or local law or regulations.

O. State Law.

Nothing in this permit shall be construed to preclude the institution of any legal action under, or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any other state law or regulation or under authority preserved by Section 510 of the Clean Water Act. Except as provided in permit conditions on "bypassing" Part II Section C. U, and "upset" (Part II Section C.V) nothing in this permit shall be construed to relieve the permittee from civil and criminal penalties for noncompliance.

P. Oil and Hazardous Substance Liability.

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under Sections 62.1-44.34:14 through 62.1-44.34:23 of the State Water Control Law.

Q. Proper Operation and Maintenance.

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes effective plant performance, adequate funding, adequate staffing, and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of this permit.

R. Disposal of solids or sludge

Solids, sludge or other pollutants removed in the course of treatment or management of pollutants shall be disposed of in a manner so as to prevent any pollutant from such materials from entering state waters.

S. Duty to Mitigate

The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

T. Need to Halt or Reduce Activity not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

U. Bypass

1. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of Part II Section C.U.2 and 3.
2. Notice
  - a. Anticipated bypass. If the permittee knows in advance of the need for a bypass, prior notice shall be submitted, if possible at least ten days before the date of the bypass.
  - b. Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in Part II Section C.I.
3. Prohibition of bypass.
  - a. Bypass is prohibited, and the Department may take enforcement action against a permittee for bypass, unless:
    - (1) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
    - (2) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and
    - (3) The permittee submitted notices as required under Part II Section C.U.2.
  - b. The Department may approve an anticipated bypass, after considering its adverse effects, if the Department determines that it will meet the three conditions listed above in Part II Section C.U.3.a.

V. Upset

1. An upset constitutes an affirmative defense to an action brought for noncompliance with technology based permit effluent limitations if the requirements of Part II Section C.V.2 are met. A determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is not a final administrative action subject to judicial review.
2. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
  - a. An upset occurred and that the permittee can identify the cause(s) of the upset;
  - b. The permitted facility was at the time being properly operated;
  - c. The permittee submitted notice of the upset as required in Part II Section C.I; and
  - d. The permittee complied with any remedial measures required under Part II Section C.S.

3. In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.

W. Inspection and Entry.

The permittee shall allow the Director, or an authorized representative, upon presentation of credentials and other documents as may be required by law, to:

1. Enter upon the permitted premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
4. Sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by the Coal Surface Mining Operation permit, Clean Water Act and the State Water Control Law, any substances or parameters at any location.

For purposes of this section, the time for inspection shall be deemed reasonable during regular business hours, and whenever the facility is discharging. Nothing contained herein shall make an inspection unreasonable during an emergency.

X. Permit Actions.

Permits may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

Y. Transfer of permits.

Permits are not transferable to any person except after approval of a succession application by the Department.

Z. Severability.

The provisions of this permit are severable, and if any provision of this permit or the application of any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances and to the remainder of this permit shall not be affected thereby.

AA. Water Quality Criteria Reopener

This permit may be modified or alternatively revoked and reissued to incorporate appropriate limits provided regular or conditional effluent monitoring indicates the need for any water quality-based limitations.

**NPDES Permit Definitions**

- (A) The term “acid or ferruginous mine drainage” means mine drainage which, before any treatment, either has a pH of less than 6.0 or a total iron concentration equal to or more than 10 mg/l.
- (B) The term “active mine drainage” means the area actively being used or disturbed for the extraction, removal, or recovery of coal from its natural deposits. This excludes areas where reclamation and revegetation has been completed.
- (C) The term “alkaline mine drainage” means mine drainage which, before any treatment, has a pH equal to or more than 6.0 and a total iron concentration less than 10 mg/l.



- (D) “Application” means the EPA standard national forms for applying for a permit, including any additions or modifications to the forms; or forms approved by EPA for use in approved States, including any approved additions or modifications.
- (E) “Approved program or approved State” means a State administered NPDES program which has been approved or authorized by EPA under 40 CFR Part 123.
- (F) “Best management practices” (BMP) means schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the United States. BMPs include treatment requirements, operation procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage.
- (G) “Coal preparation plant” means a facility where coal is crushed, screened, sized, cleaned, dried, or otherwise prepared and loaded for transit to a consuming facility. “Coal preparation plant associated areas” means the coal preparation plant yards, immediate access roads, coal refuse piles, and coal storage piles and facilities. “Coal preparation plant water circuit” means all pipes, channels, basins, tanks, and all other structures and equipment that convey, contain, treat, or process any water that is used in coal preparation processes within a coal preparation plant.
- (H) The term “commingled discharge” means discharges of drainage from underground workings that are mixed or commingled with surface mine drainage.
- (I) “Composite sample” means a combination of individual samples of wastewater taken at 1 hour intervals, for eight (8) hours (or for the duration of discharge, whichever is less), to minimize the effect of variability of the individual samples. Individual samples must be of equal volume. (Example: one (1) liter per hour.)
- (J) The term “controlled discharge” means any surface mine drainage that is pumped or siphoned from the active mining area.
- (K) “CWA” means the Clean Water Act (formerly referred to as the Federal Water Pollution Control Act) Public Law 92-500 as amended by Public Law 95-217, and Public Law 95-576, 33 U.S.C. 1251 et seq.
- (L) The “daily maximum” discharge means the total mass of a pollutant discharged during the calendar day. Where the pollutant is limited in terms other than mass, the daily maximum shall mean the average concentration or other measurement specified during the calendar day or other specified sampling day.
- (M) The “instantaneous maximum” means the level not to be exceeded at any time in any grab sample.
- (N) “Discharge (of a pollutant)” means any addition of any pollutant or combination of pollutants to waters of the United States from any point source; or any addition of any pollutant or combination of pollutants to the waters of the contiguous zone or ocean from any point source other than a vessel or other floating craft which is being used as a means of transportation.
- (O) “Existing source or existing discharger (in the NPDES program)” means any source which is not a new source or new discharger.
- (P) “Effluent limitation” means any restriction imposed by the Director on quantities, discharge rates, and concentrations of pollutants that are discharged from point sources into waters of the United States, the waters of the contiguous zone, or the ocean.
- (Q) “Effluent limitation guideline” means a regulation published by the Administration under Section 304(b) of the CWA to adopt or revise effluent limitations.
- (R) “Environmental Protection Agency (EPA)” means the United States Environmental Protection Agency.

- (S) “Estimate” means to be based on technical evaluation of the sources contributing to the discharge including, but not limited to, pump capabilities, water meters, and batch discharge volumes.
- (T) “Grab sample” means an individual sample collected in less than 15 minutes.
- (U) “Measured Flow” means any method of liquid volume measurement the accuracy of which has been previously demonstrated in engineering practices, or for which a relationship to absolute volume has been obtained.
- (V) “Mine drainage” means any drainage, and any water pumped or siphoned, from an active mining area or a post-mining area. The abbreviation “ml/l” means milliliters per liter.
- (W) The “monthly average” discharge means the total mass (and concentration if appropriate) of all daily discharges sampled and/or measured properly during a calendar month divided by the number of daily discharges sampled and/or measured properly during such month.
- (X) The “monthly average” temperature means the arithmetic mean of temperature measurements made on an hourly basis, or mean value plot of the record of a continuous automated temperature recording instrument, either during a calendar month, or during the operating month if flows are of shorter duration.
- (Y) “National Pollutant Discharge Elimination System (NPDES)” means the national program for issuing, modifying, revoking and reissuing, terminating, monitoring, and enforcing permits and imposing and enforcing pretreatment requirements, under Sections 307, 318, 402, and 405 of CWA. The term includes an approved program.
- (Z) “New discharger” means any building, structure, facility, or installation: (A) From which there is or may be a new or additional discharge of pollutants at a site at which on October 18, 1972, it had never discharged pollutants; (B) Which has never received a finally effective NPDES permit for discharges at that site; and (C) Which is not a “new source”. This definition includes an indirect discharger, which commences discharging into waters of the United States. It also includes any existing mobile point source, such as an offshore oil drilling rig, seafood processing vessel, or aggregate plant that begins discharging at a location for which it does not have an existing permit.
- (AA) “NA” means effluent limitations and monitoring requirements not required.
- (BB) “NL” means no limitation on the affected parameters, however monitoring is required.
- (CC) “Outfall” means a point source.
- (DD) “Permit” means an authorization, license, or equivalent control document issued by EPA or an approved State to implement the requirements of 40 CFR Parts 122, 123, and 124.
- (EE) “Point source” means any discernible, confined, and discrete conveyance, including but not limited to any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, vessel, or other floating craft from which pollutants are or may be discharged. This term does not include return flows from irrigated agriculture.
- (FF) “Pollutant” means dredged spoil, solid waste, incinerator residue, filter backwash, sewage, garbage, sewage sludge, munitions, chemical waste, biological materials, radioactive materials [except those regulated under the Atomic Energy Act of 1954, as amended (42 U.S.C. Section 2011 et seq.)], heat wrecked or discarded equipment, rocks, sand, cellar dirt and industrial, municipal, and agriculture waste discharged into water.

- (GG)** The term “post-mining area” means: (1) A reclamation area or (2) the underground workings of an underground coal mine after the extraction, removal, or recovery of coal from its natural deposit has ceased and prior to bond release.
- (HH)** The term “10-year, 24-hour precipitation event” means the maximum 24-hour precipitation event with a probable recurrence interval of once in ten years as defined by the National Weather service and Technical Paper No. 40, “Rainfall Frequency Atlas of the U.S.,” May 1961, or equivalent regional or rainfall probability information developed there from.
- (II)** The term “qualifying rainfall event” means the rainfall amounts as defined; active mine areas = 0.2”/24 hours, refuse areas = 2.5”/24 hours, controlled and commingled = 4.4”/24 hour.
- (JJ)** The term “reclamation area” means the surface area of a coal mine which has been returned to required contour and on which revegetation (specifically seeding or planting) work has commenced. The term “pre-reclamation area” means the surface area of a coal mine prior to reclamation.
- (KK)** The term “settleable solids” is that matter measured by the volumetric method that is determined by the following procedure: (a) fill an Imhoff cone to the one-liter mark with a thoroughly mixed sample. Allow to settle undisturbed for 45 minutes. Gently stir along the inside surface of the cone with a stirring rod. Allow to settle undisturbed for 15 minutes longer. Record the volume of settled material in the cone as milliliters per liter. The method detection limit for coal mining point sources is 0.4 ml/l.
- (LL)** The terms “treatment facility” and “treatment system” means all structures which contain, convey, and as necessary, physically or chemically treat coal mine drainage, coal preparation process water, surface runoff from disturbed areas, or drainage from coal preparation plant associated areas, which remove pollutants regulated by the Part from such waters. This includes all pipes, channels, ponds, basins, tanks, and all other equipment serving such structures.
- (MM)** The terms “underground mine drainage or discharge” mean discharges from the underground workings of underground mines until SMCRA bond release.
- (NN)** The “weekly average” discharge means the total concentration and mass of all daily discharges sampled and/or measured during a calendar week divided by the number of daily discharges sampled and/or measured during such week.
- (OO)** The term “coal refuse disposal pile” means any coal refuse deposited on the earth and intended as permanent disposal or long term storage (greater than 180 days) of such material, but does not include coal refuse deposited within the active mining area or coal refuse never removed from the active mining area.

**Section D**  
**Other Permit Requirements**

**NPDES Permit Special Conditions**

**(AA) Water Quality Monitoring**

The Department may require every owner to furnish such plans, specifications, or other pertinent information as may be necessary to determine the effect of the discharge on the water quality or such information as may be necessary to accomplish the purposes of the CWA, including but not limited to chemical and biological testing. The permittee shall obtain and record such information on the receiving waters as requested by the Department. The information shall be subject to inspection by authorized State and Federal representatives and shall be submitted with such frequency and in such detail as requested by the Department.

**(BB) Management Requirements**

1. All discharges authorized by this NPDES permit shall be made in accordance with the terms and conditions of the permit. The Department must be notified at least thirty (30) days prior to all expansions, production increases, or process modifications that will result in new or increased discharge(s) of pollutant(s). Notification should be by submission of a new or revised CSMO/NPDES application, or, if such discharge(s) does not violate effluent limitations specified in the permit, by submission to the Department of notice of such new or increased discharge of pollutant(s). All expansions, production increases, or process modifications that will result in new or increased discharge(s) of pollutant(s) must be approved by the Department prior to implementation.
2. The discharge of any pollutant limited in the permit more frequently than, or at a level greater than that identified and authorized by this permit, shall constitute a violation of the terms and conditions of this permit.
3. The discharge of any pollutant(s) from this facility that enters into a water body with an existing and approved Total Maximum Daily Load (TMDL) must be made in compliance with the TMDL and any applicable TMDL implementation plan. If the discharge enters into a water body included on the state's current 303(d) list not having an existing and approved TMDL, the discharge of any pollutant(s) from this facility cannot be the cause of the stream's impairment and 303(d) listing.

**(CC) Availability of Reports**

Except for data determined to be confidential under Section 308 of the Clean Water Act (CWA), all reports prepared in accordance with the terms and conditions of this permit will be available for public inspection at the Department office. As required by the Act, effluent data will not be considered confidential. Knowingly making false statement on any such report may result in the imposition of criminal penalties as provided for in Section 309 of the CWA and in Section 62.1-44.32 of the Code of Virginia.

**(DD) Permit Modification and Reissuance**

This permit shall be modified, or alternatively, revoked and reissued, to comply with any applicable effluent standard or limitation issued or approved under Section 301(b)(2)(C) and (D), 304 (b)(2), and 307 (a)(2) of the CWA, if the effluent standard or limitations so issued or approved:

- (i) Contain different conditions or is otherwise more stringent than any effluent limitation in the permit; or

(ii) Control any pollutant not limited in the permit; or

(iii) The permit as modified or reissued under this paragraph shall also contain any other requirements of the Act as applicable.

(iv) Immediately after EPA's promulgation of applicable standards or limitations, a draft permit incorporating the new requirements shall be sent to the permittee.

**(EE) State Law**

1. Compliance with this permit during its term constitutes compliance with the Virginia State Law and CWA except for any standard imposed under Section 307 of the CWA for a toxic pollutant injurious to human health.
2. State water quality standards contain an antidegradation policy that is applicable to this permit, facility, and discharge(s). Effluent limitations assigned to this permit require the operator to utilize the best available technology to treat all discharges and to protect water quality. As a condition of this permit, the permittee must take appropriate measures to comply with the antidegradation policy.
3. Nothing in this permit shall be construed to preclude the institution of any legal action under, or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any other State law or regulation or under authority preserved by Section 510 of the CWA.

**(FF) Toxic Pollutants**

If a toxic effluent standard or prohibition (including any schedule of compliance specified in such effluent standard or prohibition) is established under Section 307(a) of the CWA for a toxic pollutant which is present in the discharge and such standard or prohibition is more stringent than any limitation for such pollutant in this permit, this permit shall be revoked and reissued or modified in accordance with the toxic effluent standard or prohibition. Any effluent standard or prohibition established under Section 307(a) for a toxic pollutant injurious to human health is effective and enforceable by the time set forth in the promulgated standard, even absent permit modification.

**(GG) Chemical Treatment**

Chemical treatment is not permitted unless specified in Part I Section 5.15 of the CSMO/NPDES permit application or otherwise specifically authorized by the Department. Treatment chemicals will be utilized in accordance with manufacturer's specifications and in quantities not harmful to aquatic life.

**(HH) Alternate effluent limitations applicable to precipitation events**

The permit includes a condition which provides an exclusion of the TSS, total iron and total manganese concentration limitations during periods of runoff from a qualifying precipitation event as referenced in 40 CFR 434. However, TSS is required to be collected and reported for discharges utilizing the alternate effluent limit. The reported TSS analyses will be utilized by DMLR for waste load calculation only.

For discharges to TMDL watersheds with TSS identified as a stressor, the permit shall also comply with the applicable TMDL consistent with its assumptions and requirements. Best management practices requirements and/or offsets will be used to establish any necessary reductions to meet the

transient/aggregate waste load allocation as established in the compliance schedule included in this permit. This requirement is in addition to the technology-based effluent limitations of 40 CFR 434.

**CSMO Permit Special Conditions:**

(a) Disposal of non-coal waste onsite is prohibited.

(b) Water from sediment control ponds may be used on site for the purpose of dust suppression. Dust suppression shall be carried out as a best management practice provided that ponding or direct runoff from the site does not occur during or immediately following its application. Dust suppression shall not be employed as a wastewater disposal method

(c) No disturbance is allowed within any jurisdictional waters, whether water of the United States or waters of the Commonwealth of Virginia (including jurisdictional isolated waters), without first obtaining a Section 404 of the Clean Water Act (CWA) permit from the U.S. Army Corps of Engineers and / or a Section 401 of the CWA Certification from the Virginia Department of Environmental Quality.

(d) Prior to disturbing any area not included in the approved permit an application for a permit revision / amendment must be submitted to the Virginia Department of Energy / Division of Mined Land Repurposing(DMLR) and the application must be approved with appropriate fees and bond submitted to DMLR.

(e) The Department shall conduct reviews of the approved permit pursuant to 4VAC25-130-774.11. Based upon the Department review DMLR may order the revision of the permit pursuant to 4VAC25-130-774.11(b) and (c).

(f) Biological surveys will be conducted in accordance with the language in Part II Section A.E Stream Monitoring Conditions of the NPDES permit.

(g) To ensure continuing decrease in TDS for the Cumulative Impact Area, best management practices (BMPs), verified offsets, and/or mitigation activities proposed in Part II Section A.D of the NPDES permit should be completed prior to or concurrent with commencement of mining on the proposed permit.

**TMDL Special Conditions:**

**(a) TMDL Reopener Clause**

This permit shall be modified or alternately revoked and reissued if any approved waste load allocation procedure, pursuant to Section 303(d) of the CWA, imposes waste load allocations, limits or other conditions on the facility that are not consistent with the requirements of this permit.

**(b) Numeric Effluent Limitation - Annual Wasteloads**

The permittee shall ensure that discharges from permitted point sources comply with the concentration based numeric effluent limitations assigned in Part II Section A of the joint CSMO/NPDES Permit and that permitted point source discharges shall not exceed the numeric waste loads of pollution defined in this permit.

1. Tracking of mining waste loads, waste load offsets, calculations of mining waste loads, and comparisons of mining waste loads to allocations will be performed by the Department's TMDL system. Discharges resulting in a total waste load which exceeds TMDL limits will be determined as described in the factsheet associated with this permit.

2. If the Department determines that waste loads from the permitted point sources have resulted in or will result in a waste load in excess of the TMDL WLAs, the Department will require the permittee to conduct additional monitoring according to a schedule established by the Department. Based upon the monitoring results, the Department will confer with the permittee to develop reduction actions that may include revised and additional BMPs, as well as flow measurements and other monitoring. If within 90 days of receipt of the final required monitoring results the Department and the permittee cannot come to agreement on the necessary reduction actions and a schedule for their implementation, then the Department may modify or revoke and reissue the NPDES permit to assign permit-specific reduction actions and an implementation schedule. Failure by the permittee to comply with any such permit requirements will constitute grounds for enforcement.

**(c) Waste load Offset Credit**

The Department will use its existing TMDL database and software to maintain the accounting of load reduction credit tracking.

**(d) NPDES Discharge Monitoring Plan**

Referenced in Part II Section A

**(e) Offset Monitoring Plan (if applicable)**

The offset ratio for this permit is sufficient to assure that adequate pollution reductions will be accomplished without additional monitoring requirements beyond those previously identified in this joint permit.

The offset ratio is found in the TMDL Addendum in Part I Section 6.1 of the joint CSMO/NPDES permit. The minimum offset ratio is 2:1.

**(f) Unanticipated Failure of Offset (if applicable)**

Prior to the release of any performance bond on this permit, the Department shall determine if the permittee has completed offset requirements. The offset completion timing is outlined in Part I Section 6.1 of the joint CSMO/NPDES permit. If the permittee fails to complete the required offset, an alternative offset project must be approved by the Department and implemented prior to the release of any performance bond on this permit.

**(g) Responsibility to Achieve All Effluent Limitations in Permit**

The permittee shall be responsible for achieving all concentration and loading based effluent limitations assigned by this permit. The permittee shall be responsible for implementing all best management practices and/or TMDL Waste load Reduction Actions required by this permit.

**(h) Best Management Practices**

The permittee shall be responsible for implementing applicable BMPs as noted in DMLR Guidance Memorandum 14-05 and/or BMPs included in Sections 5.15 and 6.1 of the joint permit application.

**Total Maximum Daily Load (TMDL) Compliance and Documentation:**

The Department finds that the permit will comply with the approved TMDL and the TMDL Waste Load Allocation (WLA). The permit is consistent with the TMDL WLA pursuant to 40 CFR 122.44 (d)(1)(viii)(B).





**VIRGINIA DIVISION OF MINED LAND REPURPOSING**  
**Joint CSMO/NPDES Permit Factsheet**  
**Application Number 1011619**  
**CSMO: 1601576**  
**NPDES: 0081576**

This document gives pertinent information concerning the joint Coal Surface Mining Operation (CSMO)/ National Pollutant Discharge Elimination System (NPDES) permit listed below. This permit is being processed as a **Major Source** industrial permit. The industrial discharge(s) result from the control of surface water runoff and/or groundwater discharges associated with coal mining activities.

The permit process consists of: developing permit limitations based upon the effluent limitations for coal mining promulgated by the U.S. Environmental Protection Agency set forth in 40 CFR 434, the State Water Quality Standards, Total Maximum Daily Load (TMDL) Regulations, and Storm Water guidelines.

The effluent limitations contained in this permit will maintain all applicable state and federal standards, including the Water Quality Standards of 9 VAC 25-260-00 et seq., the Virginia Coal Surface Mining and Reclamation Regulations, and TMDLs.

**1. Facility Information**

**Permittee Name:** RED RIVER COAL COMPANY, INC.

**Address:** P. O. BOX 668

**City:** NORTON **State:** VA **Zip:** 24273

**Facility:** BLACK CREEK SURFACE MINE

**Location:**

**Description:** 0.3 MILES FROM BLACKWOOD/JOSEPHINE/LAUREL GROVE

**NAD 83 Virginia State Plane South Northing:** 3531902.458

**NAD 83 Virginia State Plane South Easting:** 10261902.112

**County:** WISE

**USGS 7.5' Quadrangle:** NORTON

**Type of Mining**

Undergrd. - R P

Surf-Auger/HW Miner

Surface-Contour

Surface - Area

Surf-Steep Slop

**2. CSMO/NPDES Permit Number:**

**CSMO:** 1601576

**NPDES:** 0081576

**Permit Expiration Date:** 9/27/2026

**Former NPDES Permit Number:** N/A

**Former CSMO Permit Number:** N/A

3. **Owner Contact:**

**Operator:**  
HUMPHREYS ENTERPRISES, INC.

**Telephone:**  
(276)679-1400

4. **Administrative Dates:**

**Administratively Complete Date:** 9/23/2024  
**NPDES Reviewer:** AUTUMN PIERCE  
**NPDES Reviewer Phone:** 276-523-8100  
**Review Begin Date:** 6/27/2024  
**Public Comment Beginning Date:** 9/27/2024 (1<sup>st</sup> publication, N/A)  
**Public Comment Ending Date:** 10/27/2024 (30 days following last publication, N/A)  
**Informal Conference Dates:** N/A  
**Application Approval Date:** 11/18/2024  
**Original Permit Issue Date:** 9/27/1996

5. **Application Information:**

**Application Type:** PLANS REVISION  
**Application Description:** To add Pond T/NPDES outfall 00T.

6. **Receiving Waters Classification:**

Stream Name	Stream Code	Watershed	Basin
BLACK CREEK	130	POWELL-POWELL RIVER DORCHESTER	TENNESSEE
POWELL RIVER	2	POWELL RIVER	TENNESSEE

7. **Ambient Water Quality Description**

Background/baseline ambient water quality information on receiving streams is located in Section 5.9 of the joint permit application. None of the outfalls are limited by receiving stream flows, therefore drought flow frequencies are not provided. Available instream statistics from 6/30/2021 to 6/30/2024 are summarized below.

Instream Statistics for R-3						
Parameter	Num. Samples	Average	Std. Dev	Median	Min.	Max.
Flow (GPM)	36	61.08	71.05	36.00	2.00	360.00
Temperature (C)	36	13.19	5.52	13.00	2.00	22.00
pH (Std)	36	7.25	0.28	7.30	6.60	7.80
Total Suspended Solids (mg/l)	36	4.74	9.40	2.30	0.00	53.00
Conductivity (uS/cm)	36	322.28	45.08	330.00	160.00	380.00
Total Dissolved Solids (mg/l)	36	213.50	36.04	215.00	96.00	290.00
Iron, Total (mg/l)	36	0.61	0.47	0.50	0.10	2.60
Manganese, Total (mg/l)	36	0.16	0.10	0.10	0.00	0.40
Sulfates (mg/l)	36	64.17	20.41	62.50	12.00	140.00
Alkalinity (mg/l)	36	94.39	23.04	92.50	46.00	133.00
Acidity (mg/l)	36	0.00	0.00	0.00	0.00	0.00

Instream Statistics for BL-2						
Parameter	Num. Samples	Average	Std. Dev	Median	Min.	Max.
Flow (GPM)	70	4,441.43	3,286.41	4,000.00	450.00	19,000.00
Temperature (C)	70	13.56	6.14	13.00	3.00	24.00
pH (Std)	70	7.35	0.20	7.30	7.00	7.80
Total Suspended Solids (mg/l)	70	4.52	3.81	3.10	0.00	17.90
Conductivity (uS/cm)	70	461.01	110.85	450.50	276.00	746.00
Total Dissolved Solids (mg/l)	70	294.40	70.30	293.00	162.00	454.00
Iron, Total (mg/l)	70	0.43	0.17	0.40	0.10	0.80
Manganese, Total (mg/l)	70	0.13	0.10	0.10	0.00	0.50
Sulfates (mg/l)	70	120.64	27.71	126.00	66.00	183.00
Alkalinity (mg/l)	70	110.09	40.09	108.50	47.00	211.00
Acidity (mg/l)	70	0.00	0.00	0.00	0.00	0.00

Instream Statistics for BL-1						
Parameter	Num. Samples	Average	Std. Dev	Median	Min.	Max.
Flow (GPM)	36	4,019.97	3,210.90	3,499.00	112.00	18,500.00
Temperature (C)	36	13.03	5.90	11.00	2.00	22.00
pH (Std)	36	7.65	0.27	7.70	6.90	8.20
Total Suspended Solids (mg/l)	36	3.72	4.00	2.80	0.00	16.30
Conductivity (uS/cm)	36	444.39	85.61	452.00	260.00	605.00
Total Dissolved Solids (mg/l)	36	298.56	72.21	300.00	146.00	410.00
Iron, Total (mg/l)	36	0.26	0.21	0.20	0.00	1.00
Manganese, Total (mg/l)	36	0.03	0.04	0.00	0.00	0.10
Sulfates (mg/l)	36	121.75	26.34	125.50	64.00	169.00
Alkalinity (mg/l)	36	100.58	31.02	103.00	44.00	158.00
Acidity (mg/l)	36	0.00	0.00	0.00	0.00	0.00

Instream Statistics for ISMP-4						
Parameter	Num. Samples	Average	Std. Dev	Median	Min.	Max.
Flow (GPM)	36	3,388.25	2,932.49	2,997.00	169.00	10,000.00
Temperature (C)	36	13.36	5.49	13.00	2.00	21.00
pH (Std)	36	7.93	0.16	8.00	7.50	8.30
Total Suspended Solids (mg/l)	36	6.82	22.90	1.85	0.00	137.60
Conductivity (uS/cm)	36	1,048.94	135.98	1,045.50	581.00	1,236.00
Total Dissolved Solids (mg/l)	36	778.11	134.99	786.00	370.00	998.00
Iron, Total (mg/l)	36	0.35	0.70	0.20	0.00	4.20
Manganese, Total (mg/l)	36	0.05	0.12	0.00	0.00	0.60
Sulfates (mg/l)	36	357.14	81.11	374.00	104.00	478.00
Alkalinity (mg/l)	36	178.33	21.94	178.00	103.00	208.00
Acidity (mg/l)	36	0.00	0.00	0.00	0.00	0.00

Instream Statistics for ISMP-3						
Parameter	Num. Samples	Average	Std. Dev	Median	Min.	Max.
Flow (GPM)*	36	0.00	0.00	0.00	0.00	0.00

Instream Statistics for ISMP-2						
Parameter	Num. Samples	Average	Std. Dev	Median	Min.	Max.
Flow (GPM)	36	20,817.64	32,196.64	13,525.00	2,106.00	200,000.00
Temperature (C)	36	13.28	5.34	13.00	2.00	22.00
pH (Std)	36	7.50	0.18	7.50	7.10	7.90
Total Suspended Solids (mg/l)	36	8.72	25.47	2.40	0.00	136.60
Conductivity (uS/cm)	36	483.11	140.79	469.00	202.00	755.00
Total Dissolved Solids (mg/l)	36	301.83	104.93	310.00	22.00	510.00
Iron, Total (mg/l)	36	0.50	0.83	0.30	0.20	4.50
Manganese, Total (mg/l)	36	0.09	0.08	0.10	0.00	0.40
Sulfates (mg/l)	36	119.61	42.31	114.50	33.00	193.00
Alkalinity (mg/l)	36	109.33	36.86	109.50	44.00	183.00
Acidity (mg/l)	36	0.00	0.00	0.00	0.00	0.00

Instream Statistics for ISMP-1						
Parameter	Num. Samples	Average	Std. Dev	Median	Min.	Max.
Flow (GPM)	69	16,595.71	26,307.71	9,000.00	2,352.00	210,000.00
Temperature (C)	69	12.99	5.82	12.00	1.00	23.00
pH (Std)	69	7.84	0.22	7.80	7.30	8.40
Total Suspended Solids (mg/l)	69	5.54	16.29	2.00	0.00	119.40
Conductivity (uS/cm)	69	610.93	153.46	595.00	299.00	885.00
Total Dissolved Solids (mg/l)	69	423.39	124.85	416.00	168.00	640.00
Iron, Total (mg/l)	69	0.32	0.52	0.20	0.10	3.40
Manganese, Total (mg/l)	69	0.03	0.07	0.00	0.00	0.40
Sulfates (mg/l)	69	162.74	42.42	172.00	71.00	275.00
Alkalinity (mg/l)	69	123.80	33.65	124.00	58.00	187.00
Acidity (mg/l)	69	0.00	0.00	0.00	0.00	0.00

**8. Permit Characterization/Special Conditions/Effluent Limitations:**

Narrative Water Quality Standards Applicable

9VAC25-260-20

Discharges from this operation must not cause the violation of any applicable narrative instream water quality standards.

Technology-based Effluent Limitations Applicable

40 CFR 434

Numeric Water Quality based Effluent Limitations Applicable

9VAC25-260-140

Discharges from this operation must not cause the violation of any applicable numeric instream water quality standards.

SMCRA Performance Standard

4VAC25-130-816.42 and/or 4VAC25-130-817.42

Standard Permit Conditions Applicable

40 CFR 122.41 and 9VAC25-31-190

The outfalls, discharges, and related activities associated with the proposed operation must individually and in aggregate remain in compliance with the requirements stated in sections 318, 402, and 405 of the Clean Water Act. Additionally, the permittee must comply with all conditions attached to the permit, including but not limited to the effluent standards established under 307(a) of the Clean Water Act. The permittee is bound to all duties, procedures, and requirements laid out in both Federal Regulation 40 CFR 122.41 and State Regulation 9VAC25-260.

Special Permit Conditions – TMDL Watershed

40 CFR 130 and CWA 303(d)

The application includes outfalls and/or discharges falling within established boundaries of the TMDL Watershed(s) Black Creek due to established stressor(s) MN and Powell River due to established stressor(s) TSS. Therefore, special permit conditions as defined in the regulations cited above are applicable to the permit.

Special Permit Conditions – SMCRA

4VAC25-130-773-17

Special Permit Conditions – Alternate Effluent Limitations: Remining  
4VAC25-130-825

Discharges limited based on receiving stream flow – Mixing Zone  
9VAC260-20

Possible Interstate Effect  
This permit is not permitted to cross state boundaries or otherwise require Virginia interstate regulations.

**9. NPDES Effluent Limitation Basis**

The monitoring frequency and sample type have been established after considering the consistency and nature of these operations, the existing analytical data and the potential environmental risk and consequences of the discharges. Reporting of monitoring data is required quarterly.

<b>Parameter</b>	<b>Basis</b>
<b>Iron, Total</b>	Iron limitations are based on 40-CFR-434.
<b>Flow</b>	Report only, no limit. Monitoring required by federal effluent guidelines (40 CFR Part 434).
<b>Manganese, Total</b>	Manganese limitations are based on 40-CFR-434.
<b>pH</b>	The pH limitation is based upon Virginia's water quality standards and federal effluent guidelines (40 CFR Part 434).
<b>Settleable Solids</b>	SS limitations are based on federal effluent guidelines for coal mining (40 CFR Part 434).
<b>Total Dissolved Solids</b>	Monitoring required for informational purposes. TDS is also load-limited based upon the approved TMDL, if applicable. For discharges to TMDL watersheds with TDS identified as a stressor, the permit shall also comply with the applicable TMDL consistent with its assumptions and requirements. Best management practices requirements and/or offsets will be used to establish any necessary reductions to meet the transient/aggregate wasteload allocation.
<b>Total Suspended Solids</b>	TSS limitations are based on federal effluent guidelines for coal mining (40 CFR Part 434). TSS is also load-limited based upon the approved TMDL, if applicable. For discharges to TMDL watersheds with TSS identified as a stressor, the permit shall also comply with the applicable TMDL consistent with its assumptions and requirements. Best management practices requirements and/or offsets will be used to establish any necessary reductions to meet the transient/aggregate wasteload allocation.

**10. Permit or Proposed Permit Area Questions**

<b>Check all that apply:</b>	
<input type="checkbox"/>	A. The area contains a publicly owned treatment works which discharge into the waters of the United States.
<input type="checkbox"/>	B. The facility treats, stores, or disposes of hazardous wastes.
<input type="checkbox"/>	C. Fluids are injected at this facility which are: (1) brought to the surface in connection with conventional oil or natural gas production; (2) used for the enhanced recovery of oil or natural gas; or (3) for storage of liquid hydrocarbons.
<input type="checkbox"/>	D. The area contains a concentrated animal feeding operation or aquatic animal production facility that discharges into the waters of the United States.
<input type="checkbox"/>	E. This facility will inject industrial effluent below the lower most stratum containing, within 1 quarter mile of the well bore, underground sources of drinking water.

**11. NPDES Outfall Description:**

Sediment control structures and the associated NPDES outfalls for surface coal mining operations primarily receive precipitation runoff from mined areas and treat the runoff by settling sediment particles prior to discharge to the receiving stream. Precipitation runoff from mined areas also dissolves portions of exposed fresh rock and carries the associated ions in solution. These ions may not be reduced in the sedimentation process prior to discharge. Certain dissolved ions or the combined concentration of these ions may cause benthic impairment depending on their makeup and/or abundance.

NPDES discharges associated with this permit are from the control of surface water runoff resulting from precipitation and/or groundwater discharges associated with coal mining activities. Typically, discharges are only treated by sedimentation, but in limited circumstances treatment may include chemical treatment such as the addition of neutralizing agents or flocculants.

There are 5 outfalls associated with this permit. Of all total outfalls, 4 were previously approved, and of all previously approved outfalls, 4 have been constructed. The constructed outfalls are G WEIR, H, IE, and S. Outfall G WEIR has historically discharged 0.0% of the time over 0 measurements. Outfall H has historically discharged 0.0% of the time over 72 measurements. Outfall IE has historically discharged 100.0% of the time with an estimated flow of 19.3 GPM over 13 measurements. Outfall S has historically discharged 0.0% of the time over 72 measurements.

NPDES Outfall T is added during this Plan Revision, Application 1011619. Due to Outfall Ts location within the watershed it is expected to discharge rarely, like similar outfalls located within the permit boundary.

**Proposed Discharges**

Outfall(s) T (is/are) added by revision. There are no outfalls deleted by this revision.

The following tables present details for each proposed and/or existing outfall. Specific information, including location, regarding each outfall and facility is also found in Section 5, Section 12, and Section 21 of the CSMO/NPDES permit.



<b>MPID Number:</b> 0005150	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 6	<b>Location Number:</b> S
Elevation: 2,340.00	Facility Location: POND S	Quad: NORTON	Northing: 3,539,408.3400
Easting: 10,262,012.4700	Watershed Acres: 126.2	Disturbed Acres: 78.8	Receiving Stream: True

<b>MPID Number:</b> 0003201	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 6	<b>Location Number:</b> G WEIR
Elevation: -999.00	Facility Location: REMG WEIR	Quad: NORTON	Northing: 3,534,787.6610
Easting: 10,262,516.7513	Watershed Acres: 123.9	Disturbed Acres: 20.9	Receiving Stream: True

<b>MPID Number:</b> 0002316	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 6	<b>Location Number:</b> H
Elevation: -999.00	Facility Location: POND H	Quad: NORTON	Northing: 3,540,740.5570
Easting: 10,269,619.7354	Watershed Acres: 167.9	Disturbed Acres: 33.7	Receiving Stream: True

<b>MPID Number:</b> 0002314	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 6	<b>Location Number:</b> IE
Elevation: -999.00	Facility Location: TMP POND E	Quad: NORTON	Northing: 3,527,671.4868
Easting: 10,259,408.4640	Watershed Acres: 282.3	Disturbed Acres: 205.8	Receiving Stream: True

<b>MPID Number:</b> 0012749	<b>Action:</b> A	<b>Sampling Freq/Qtr:</b> 6	<b>Location Number:</b> T
Elevation: 2,265.00	Facility Location: Pond T	Quad: NORTON	Northing: 3,531,126.2000
Easting: 10,262,185.7200	Watershed Acres: 38.8	Disturbed Acres: 27.9	Receiving Stream: True

**12. Instream Monitoring Description:**

Instream monitoring requirements and locations are addressed in Sections 5.7, 5.10, and 21.2 of the joint CSMO/NPDES permit. Location details for each instream monitoring site are tabulated below:

<b>MPID Number:</b> 1720020	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 3	<b>Location Number:</b> R-3
Facility Location: BELOW	Quad: NORTON	Northing: 3,524,951.4170	Easting: 10,265,063.2668
Stream: BENTLEY HOLLOW			

<b>MPID Number:</b> 0007944	<b>Action:</b>	<b>Sampling Freq/Qtr: 0</b>	<b>Location Number:</b> BC3
Facility Location: midstream	Quad: NORTON	Northing: 3,537,500.8980	Easting: 10,262,111.3200
Stream: BLACK CREEK			

<b>MPID Number:</b> 0007941	<b>Action:</b>	<b>Sampling Freq/Qtr: 0</b>	<b>Location Number:</b> BC4
Facility Location: BIO- CHEMDS	Quad: NORTON	Northing: 3,540,335.0650	Easting: 10,260,339.4190
Stream: BLACK CREEK			

<b>MPID Number:</b> 0007940	<b>Action:</b>	<b>Sampling Freq/Qtr: 0</b>	<b>Location Number:</b> BC1
Facility Location: BIO- CHEMUS	Quad: NORTON	Northing: 3,526,269.3150	Easting: 10,258,793.6680
Stream: BLACK CREEK			

<b>MPID Number:</b> 0007939	<b>Action:</b>	<b>Sampling Freq/Qtr: 0</b>	<b>Location Number:</b> PR2
Facility Location: BIO- CHEMDS	Quad: NORTON	Northing: 3,524,556.2650	Easting: 10,257,430.1980
Stream: POWELL RIVER			

<b>MPID Number:</b> 0007938	<b>Action:</b>	<b>Sampling Freq/Qtr: 0</b>	<b>Location Number:</b> PR1
Facility Location:	Quad: NORTON	Northing: 3,523,074.7180	Easting: 10,262,232.9150
Stream: POWELL RIVER			

<b>MPID Number:</b> 0004741	<b>Action:</b>	<b>Sampling Freq/Qtr: 3</b>	<b>Location Number: BL-</b> <b>2</b>
Facility Location: DOWNSTREAM	Quad: NORTON	Northing: 3,539,124.0792	Easting: 10,276,031.9051
Stream: POWELL RIVER			

<b>MPID Number:</b> 0004740	<b>Action:</b>	<b>Sampling Freq/Qtr: 3</b>	<b>Location Number: BL-</b> <b>1</b>
Facility Location: UPSTREAM	Quad: NORTON	Northing: 3,539,980.0010	Easting: 10,272,525.8889
Stream: POWELL RIVER			

<b>MPID Number:</b> 0002373	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 3	<b>Location Number:</b> ISMP-4
Facility Location: DOWNSTREAM	Quad: NORTON	Northing: 3,525,658.2223	Easting: 10,258,793.2394
Stream: BLACK CREEK			

<b>MPID Number:</b> 0002372	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 3	<b>Location Number:</b> ISMP-3
Facility Location: UPSTREAM	Quad: NORTON	Northing: 3,540,672.8807	Easting: 10,270,419.0044
Stream: BLACK CREEK			

<b>MPID Number:</b> 0002371	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 3	<b>Location Number:</b> ISMP-2
Facility Location: UPSTREAM	Quad: NORTON	Northing: 3,524,215.1496	Easting: 10,264,024.0735
Stream: POWELL RIVER			

<b>MPID Number:</b> 0002370	<b>Action:</b>	<b>Sampling Freq/Qtr:</b> 3	<b>Location Number:</b> ISMP-1
Facility Location: POWELL RIV	Quad: NORTON	Northing: 3,524,732.2100	Easting: 10,258,011.4800
Stream: POWELL RIVER			

**13. Ground Water Monitoring:**

Ground water monitoring requirements and locations are addressed in Sections 5.3, 5.6, and 21.2 of the joint CSMO/NPDES permit.

**14. Climatological Monitoring Description:**

Climatological monitoring requirements and location information are addressed in Sections 5.12 and 21.2 of the joint CSMO/NPDES permit.

**15. Threatened/Endangered Species**

For additional information regarding Threatened/Endangered Species, refer to Section 8.7 of the joint CSMO/NPDES permit application.

**16. Site Inspection:**

Site inspections are required under the Surface Mining Control and Reclamation Act (SMCRA) permit under 4 VAC 25-130-840.11.

**17. Storm Water Discharges Associated with Industrial Activity:**

All outfalls from the facility which contain storm water runoff will be subject to the storm water provisions of the NPDES program as governed by 9 VAC 25-31 et seq. The Surface Mining Control and Reclamation Act (SMCRA) permit authorized under 4 VAC 25-130 and issued jointly with this NPDES permit contains extensive storm water monitoring and management requirements which are incorporated into this NPDES permit by reference.

The management and control of all storm water discharges not covered under 9 VAC 25-31 et seq is governed by the storm water management and drainage control provisions proposed in the SMCRA permit and meet or exceed the Storm Water Pollution Prevention Plan requirements of 9 VAC 25-151-80.

**18. Anti-Degradation Review:**

Stream Tier Designation(s):

There is 1 stream designated as an affected surface water for this permit.

True has a designation of Tier I.

The State Water Control Board's Water Quality Standards includes an antidegradation policy (9 VAC 25-260-30). All state surface waters are provided one of three levels of antidegradation protection. For Tier 1 or existing use protection, existing uses of the water body and the water quality to protect these uses must be maintained. Tier 2 water bodies have water quality that is better than the water quality standards. Significant lowering of the water quality of Tier 2 waters is not allowed without an evaluation of the economic and social impacts. Tier 3 water bodies are exceptional waters and are so designated by regulatory amendment. The antidegradation policy prohibits new or expanded discharges into exceptional waters.

**19. Anti-Backsliding:**

For permit renewals and(or) permit modifications, the effluent limitations included in the permit are at least as restrictive as those in the preceding permit.

**20. Permit Conditions:**

Refer to the standard conditions and special conditions contained in the joint CSMO/NPDES permit.

The following special conditions are proposed to be included in Sections C and D of the NPDES permit:

- a. **Industrial Reopener.** The permit includes a standard reopener to address potential changes in the permit which may be required as a result of changes in effluent standards or limitations promulgated or approved under Section 307(a)(2) of the Clean Water Act. (Part I.B.1) [Section C]

**Rationale:** 40 CFR 122.44 requires all permits for primary industrial categories to include the requirements of Section 307(a)(2) of the Clean Water Act.

- b. **Notification Levels:** The permit includes a special condition which requires the permittee to notify the Department if they discharge certain toxic pollutants above established concentrations. [Section C]

**Rationale:** Required by VPDES Permit Regulation, 9 VAC 25-31-200 A for all manufacturing, commercial, mining, and silvicultural dischargers.

- c. **TMDL Reopener.** The permit includes a standard reopener to address potential changes in the permit which may be required as a result of a new or revised TMDL. [Section D]

**Rationale:** Section 303(d) of the Clean Water Act requires that Total Maximum Daily Loads (TMDLs) be developed for streams listed as impaired. This special condition is to allow the permit to be reopened if necessary to bring it into compliance with any applicable TMDL approved for the receiving stream. The reopener recognizes that, according to Section 402(o)(1) of the Clean Water Act, limits and/or conditions may be either more or less stringent than those contained in this permit. Specifically, they can be relaxed if they are the result of a TMDL, basin plan, or other waste load allocation prepared under section 303 of the Act.

**It is believed that the joint CSMO/NPDES permit effluent limitations and special conditions will maintain State water quality standards.**

21. **Materials Storage:**

See Special Condition (p) 2 of the standard NPDES Permit Conditions in the NPDES Permit, Section C.

22. **NPDES Permit Rating Worksheet:**

The staff has completed the NPDES Permit Rating Worksheet and has determined that the facility meets the criteria to be classified as a Major Source. The completed worksheet is included in Appendix V.

Total Score: 540

23. **Detailed Description - Location of Discharge Point(s)**

Reference the mapping included in Section 21.2 of the permit application.

24. **Public Participation:**

**Public Notice Information:**

Public Notice required.

A copy of the application materials is made available for public inspection and comment at the designated public office. A copy of the draft NPDES permit and fact sheet are available for public inspection and comment at the Division's Big Stone Gap office.

NPDES Permit Renewal/Modification

Public notice requires publication for 1 week in a newspaper of general circulation. The public comment period runs 30 days following the date of publication. Refer to Sections 2.6 and 2.7 of the joint CSMO/NPDES permit.

New Joint Permit, CSMO/NPDES Permit Renewal, or Significant Revision

Public notice requires publication for 4 consecutive weeks in a newspaper of general circulation. The public comment period runs 30 days following the date of last publication. Refer to Sections 2.6 and 2.7 of the joint CSMO/NPDES permit.

**Public Comment Beginning Date:**

9/27/2024 (1<sup>st</sup> publication, N/A)

**Public Comment Ending Date:**

10/27/2024 (30 days following last publication)

**Public Comment Information:**

Any person whose interests are or may be adversely affected by the proposed operation, or an Officer, or Head of any Federal, State, or local government agency or authority may within 30 days of the date of fourth publication may submit written comments or objections to the Division of Mined Land Reclamation concerning the proposed operation (and may also request, in writing, that the Division hold an Informal Conference concerning the application).

Any relevant comments received during the public comment period or provided during an Informal Conference are addressed in writing and provided to those who comment. Comments that were received after the public comment period were considered during the technical review process.

**Procedures for requesting an informal conference:**

A request for an informal conference shall follow the requirements of 4 VAC 25-130-773.13(c) of the Virginia Coal Surface Mining Reclamation Regulations.

All correspondence concerning the application should be submitted to:

Virginia Department of Energy  
Attn: DMLR Permit Section  
3405 Mountain Empire Rd  
Big Stone Gap, VA 24219

Telephone: (276) 523-820 - Attn: DMLR Permit Section

Written comments and a request for informal conference may be e-mailed to the Division at [dmlrpublicnotice@dmme.virginia.gov](mailto:dmlrpublicnotice@dmme.virginia.gov)

**Procedures for requesting a formal hearing:**

4VAC25-130-775.11(g)

Administrative review:

Within 30 days after an applicant or permittee is notified of the decision of the division concerning an application for approval of exploration required under Part 772, a permit for surface coal mining and reclamation operations, a permit revision, a permit renewal, or a transfer, assignment, or sale of permit rights, the applicant, permittee, or any person with an interest which is or may be adversely affected by the decision may request, in writing, a formal public hearing to contest such action with the Director of the Division of Mined Land Reclamation:

Virginia Department of Energy  
Attn: Director of the Division of Mined Land Repurposing  
3405 Mountain Empire Rd  
Big Stone Gap, VA 24219

**Procedures for judicial review:**

4VAC25-130-775.13:

Judicial review

(a) General. Any applicant, or any person with an interest which is or may be adversely affected by the final administrative decision and who has participated in the administrative hearings as an objector may appeal as provided in subsection (b) of this section if—

(1) The applicant or person is aggrieved by the director or his designee's final order under 4VAC25-130-775.11; or

(2) Either the division or the director failed to act within time limits specified in 4VAC25-130-775.11.

(b) Judicial review. The final order of the division pursuant to subsection (a) of 4VAC25-130-775.11 shall be subject to judicial review as provided by the Virginia Administrative Process Act and the rules of the Supreme Court of Virginia as promulgated thereto. The availability of such review shall not be construed to limit the operation of the rights established in Section 520 of the Federal Act.

(c) All notices of appeal for judicial review of a hearing officer's final decision, or the final decision on review and reconsideration, shall be filed with the Director, Division of Mined Land Reclamation:

Virginia Department of Energy  
Attn: Director of the Division of Mined Land Repurposing  
3405 Mountain Empire Rd  
Big Stone Gap, VA 24219

**25. Variations**

This permit has applicable waiver variations. The permit standards with waivers and variations are as follows:

- Mining within 100 ft. of a stream
- Within 300 ft. of occupied dwellings
- Contemporaneous Reclamation
- Within 100 ft. of public road
- Within 500 feet of abandoned U.G. Mine Works
- Within 500 feet of active U.G. Mine Works
- Small area drainage

**26. Staff Comments**

Staff comments and applicant responses are located in Section 21.3 of the joint CSMO/NPDES permit.

**27. Impaired Segments/TMDL Watersheds**

TMDL Wasteload Evaluation:

Aggregate/transient mining wasteloads for each TMDL watershed and stressor are calculated on a quarterly basis by the DMLR staff using reported monitoring data (including measurements taken when utilizing applicable AELs) .These wasteload evaluations include each permit's contribution to the total TMDL wasteload. If the total TMDL wasteload exceeds the wasteload balance provided in the approved TMDL document, individual wasteload reductions for each permit are also calculated.

Wasteload evaluations for TMDL watersheds applicable to this permit are summarized in this factsheet. Full wasteload evaluation documents are posted on the web at: <https://www.dmme.virginia.gov/DMLR/TMDLWasteLoadEvaluation.shtml>.

TMDL Summary for Permit 1601576 / 0081576 :

There are 2 TMDL area which contain a wasteload allocation for active coal mining facilities affected by the outfalls of this permit - Black Creek and Powell River. The outfalls G WEIR, IE, and S on this permit are previously approved to discharge into the Black Creek Watershed. The outfall T is proposed to discharge into the Black Creek Watershed by this application. The outfalls G WEIR, H, IE, and S on this permit are previously approved to discharge into the Powell River Watershed.



Black Creek MN TMDL Summary

<b>Black Creek MN Wasteload Evaluation Summary for Q1 2024</b> 4/1/2023 to 3/31/2024	
<b>Watershed Wasteload Allocation for Mining Operations (kg/year):</b>	2,127.00
<b>Current Watershed Wasteload from Mining Operations (kg/year):</b>	60.55
<b>Mining Wasteload Balance (kg/year):</b>	2,066.45
<b>Permit Wasteload (kg/year):</b>	0.00
<b>Permit Wasteload Reduction Target (kg/year):</b>	0.00
<b>Est. Wasteload Change Due to this Application (kg/year):</b>	46.32
<b>Permit Offset Required (kg/year):</b>	0.00

Based on the Black Creek MN wasteload evaluation from 04/01/2023 to 03/31/2024, the aggregate/transient mining wasteload does not exceed the wasteload allocation. Therefore, the associated NPDES permit does not require the permittee to implement BMPs and/or offsets to reduce future MN wasteloads in the Black Creek watershed.

The estimated wasteload change due to this revision is not predicted to cause the watershed wasteload to exceed the allocation. Therefore, no offset is required for this permit.

Powell River TSS TMDL Summary

<b>Powell River TSS Wasteload Evaluation Summary for Q1 2024</b> 4/1/2023 to 3/31/2024	
<b>Watershed Wasteload Allocation for Mining Operations (kg/year):</b>	845,180.00
<b>Current Watershed Wasteload from Mining Operations (kg/year):</b>	187,825.67
<b>Mining Wasteload Balance (kg/year):</b>	657,354.33
<b>Permit Wasteload (kg/year):</b>	0.00
<b>Permit Wasteload Reduction Target (kg/year):</b>	0.00
<b>Est. Wasteload Change Due to this Application (kg/year):</b>	1,350.95
<b>Permit Offset Required (kg/year):</b>	0.00

Based on the Powell River TSS wasteload evaluation from 04/01/2023 to 03/31/2024, the aggregate/transient mining wasteload does not exceed the wasteload allocation. Therefore, the associated NPDES permit does not require the permittee to implement BMPs and/or offsets to reduce future TSS wasteloads in the Powell River watershed.

The estimated wasteload change due to this revision is not predicted to cause the watershed wasteload to exceed the allocation. Therefore, no offset is required for this permit.

TMDL Offset Tracking and Evaluation

If an offset is required, the Department will track approved offset balances for this permit utilizing the Department's TMDL system. If the permit is required to have a mining waste load offset in order to discharge, then the following requirements will also be applied.

1. Permit compliance will be determined by comparing the rolling annualized aggregate mining waste load to the offset limitations. The permit will not be allowed to exceed the mining waste load offset amount credited to this permit except as described below:

- a. Provided excess mining waste load is available when the aggregate watershed mining waste load is compared to the TMDL mining waste load allocation, the excess may be applied to the permitted waste load for that particular quarter.
  - b. On the condition of the rolling annualized aggregate waste load exceeding the offset limitation, then the permittee may request that additional available offset credit be applied to the permit.
2. If no excess mining waste load is available and no existing offset credit is available, then the excess mining waste load amount from this permit must have an additional offset. The additional offset must be reviewed and approved by the Department.

### Future Growth

The Department will track the future growth balance for TMDL watersheds. The future growth allocation will be managed in a manner similar to an offset where new applications will draw from future growth if mining waste load is not available for the watershed. If the future growth is utilized as well as the mining waste load for the watershed, the permit will be required to have a mining waste load offset in order to discharge.

### PCBs

The permit is not expected to have a direct effect within the Levisa River watershed; therefore, PCB monitoring is not mandated for the permit.

## **List of Appendices**

1. Appendix I: Representative Sampling/Effluent Screening
2. Appendix II: Evaluation of Effluent Limitations
3. Appendix III: Reasonable Potential Analysis
4. Appendix IV: Evaluation of Alternate Effluent Limitations- Remining
5. Appendix V: NPDES Major/Minor Permit Rating Worksheet
6. Appendix VI: TMDL Wasteload Change Estimations

## **Appendix I. Representative Sampling/Effluent Screening:**

### **Representative Sampling**

Typical surface mine discharges can be divided into three categories based on the area controlled and whether the outfall is expected to discharge continuously, intermittently, or rarely/never.

Discharges within each of the three categories are located in the same geological strata and receive precipitation runoff from the same sources. Due to the similarities between discharges within each classification, the Department is allowing representative sampling from one outfall of each class with the exception of outfalls expected to rarely/never discharge, which require no representative sampling. Initial permit conditions will be imposed based on the representative data. Permit limits will be modified as appropriate at renewal once discharge data is collected from the outfall when constructed. If any outfalls begin to have frequent discharges then representative sampling will be required and any necessary permit limits will be developed. If the representative outfall is not constructed first or is not the first outfall of the type represented to discharge, the first discharging outfall should be utilized.

### **Effluent Screening**

#### WET Assays – Effluent

WET assays are utilized as a screening tool to determine if a reasonable potential for effluent toxicity exists. Acute and/or chronic bioassays as appropriate will be utilized to measure whole effluent toxicity in discharge samples for four consecutive quarters. Effluents demonstrating toxicity will receive appropriate WET limits for the discharge. Discharges not exhibiting toxicity will not receive WET limits and will only be required to submit additional WET tests at renewal and/or mid-term. Characterization will be conducted by a qualified laboratory per DEQ protocol. WET assays will utilize standard WET testing organisms and toxicity will be determined utilizing the results from such testing.

WET testing is not required for this permit.

#### Chemical Analyses – Effluent

The permit requires sampling for the parameters in Table 1 within 6 months of commencing the permitted activity and at renewal for each representative outfall, and in receiving streams. If any outfalls begin to have frequent discharges then representative sampling will be required and any necessary permit limits will be developed. If the representative outfall is not constructed first or is not the first outfall of the type represented to discharge, the first discharging outfall should be utilized. This chemical effluent screening data will be utilized for the RP and appropriate numerical limits will be applied if necessary. These parameters will be compared to instream baseline data and numerical water quality standards to determine whether numerical limits and/or mixing zones are required. The chemical analyses for effluent screening are in addition to the currently required bi-weekly sampling required for NPDES monitoring compliance purposes.

Effluent screening is not required for this permit.

## TABLE 1 - Parameters

### Parameter

Flow (gpm)  
Temperature (°C)  
pH (std units)  
TSS (mg/L)  
Specific Conductance (uS/cm)  
TDS (mg/L)  
Sulfates (mg/L)  
Bromide (mg/L)  
Chlorides (mg/L)  
Aluminum (mg/L)  
Iron (mg/L)  
Manganese (mg/L)  
Magnesium (mg/L)  
Total Acidity (mg/L)  
Total Alkalinity (mg/L CaCO<sub>3</sub>)  
Bicarbonate Alkalinity (mg/L)  
Carbonate Alkalinity (mg/L)  
Hardness (mg/L CaCO<sub>3</sub>)  
Total Zinc (µg/L)  
Total Antimony (µg/L)  
Total Arsenic (µg/L)  
Total Beryllium (µg/L)  
Total Cadmium (µg/L)  
Total Chromium (µg/L)  
Total Copper (µg/L)  
Total Lead (µg/L)  
Total Mercury (µg/L)  
Total Nickel (µg/L)  
Total Selenium (µg/L)  
Total Silver (µg/L)  
Total Thallium (µg/L)  
Total Barium (µg/L)  
Total Boron (µg/L)  
Total Cobalt (µg/L)  
Total Cyanide (µg/L)  
Total Phenols (µg/L)  
Nitrate (mg/L)  
Nitrite (mg/L)  
Dissolved Organic Carbon (mg/L)  
Hydrogen Sulfide (mg/L)<sup>1</sup>

<sup>1</sup> This parameter need only be analyzed for underground mine discharges.

## **Appendix II: Evaluation of Effluent Limitations**

Sediment control structures and the associated NPDES outfalls for surface coal mining operations primarily receive precipitation runoff from mined areas and discharge in response to precipitation events. Technology-based effluent limitations per 40 CFR 434 apply.

None Requested.

### **Appendix III: Reasonable Potential Analysis**

DMLR must perform a Reasonable Potential Analysis (RPA) (9VAC 25-31-220 D.1) for each proposed discharge in determining which permit conditions are needed for a new or expanded discharge permit. This analysis is based primarily on the potential for the permit's sediment control structures to discharge and upon the nature of the discharge, whether or not dilution is available in the receiving streams, mining practices, including the geology, drainage area, etc. DMLR may utilize applicable WET screening data, effluent chemical monitoring data, instream chemical data, and instream biological survey data in conducting the RPA. As part of any RPA, DMLR will consider whether or not there are representative discharges that can be used to determine the RP for a given outfall. In TMDL watersheds, DMLR will consider whether discharges will comply with the TMDL as a portion of the RPA.

In summary, Virginia's approach will include some or all of these measures to address the potential impact of mining discharges and to address Virginia's Narrative Water Quality Standards.

1. The potential for discharge, including both flow rate and duration
2. Chemical characterization of discharges and receiving streams
3. Instream biologic characterization including benthic surveys, fish surveys, chemical water quality analyses, and habitat surveys to address effects on sensitive species
4. WET assays to determine effluent toxicity when deemed necessary by DMLR

Reasonable Potential was conducted in Renewal Application 1011100 and 1011092, issued 11/17/2021. This analysis found Outfall D and G have reasonable potential to exhibit acute and chronic toxicity.

Outfall D was removed from permit on 6/17/2024 via inspector plan modification per permit reclamation requirements. Since Outfall D controlled runoff from permit area released from permit boundary, no additional outfalls require Acute or Chronic WET Testing.

Proposed NPDES Outfall T is unlikely to discharge due to location within the watershed. therefore, Outfall T is unlikely to exhibit Acute or Chronic toxicity.

### **Instream Biological Surveys**

Biological Monitoring Plan

Biological surveys are to be completed to determine the benthic health of POWELL RIVER at locations PR1 and PR2 and BLACK CREEK at locations BC1, BC4, and BC3 as outlined in the joint CSMO/NPDES permit. Fall annual biological monitoring at Biological Aquatic Stations BC1, BC3, BC4, PR1, and PR2 is required (See Part I Section 8.3 and the applicable map in Part I Section 21.2 in the DMLR Electronic Permit Application for location information). The Virginia Stream Condition Index (VASCI) protocol will be used. Also, stream habitat scores and chemical data will be collected at these locations. All biologic sampling shall be done in accordance with the Virginia Department of Wildlife Resources scientific collection permit requirements.

**Appendix IV: Evaluation of Alternate Effluent Limitations: Remining**  
None Requested.



**Appendix V: NPDES Permit Rating Worksheet**

**Date: 11 February 2025**

**DMLR Application No: 1011619**

**DMLR Permit No: 1601576**

**VPDES Permit No: 0081576**

**FACTOR 1 Toxic Pollutant Potential**

Determine the *Total Toxicity* potential:

SICCode	Permit Has Prep Plant	Total Toxicity Group	Points
1221		5	25
1221	X	5	25
1222		5	25
1222	X	6	30

**Factor 1 Score: 25**

**FACTOR 2 Flow/Stream Flow Volumes**

Coal industry discharges are always Type III

Sum of average discharges for each outfall for permit: 0.88 MGD

Flow Class	Code	Points
< 1 MGD	31	0
< 5 MGD	32	10
<10 MGD	33	20
>10 MGD	34	30

**Factor 2 Score: 0**

**FACTOR 3 Conventional Pollutants**

TSS load for all outfalls on permit

<b>Flow (gpm):</b>	25.00
<b>Concentration (mg/L):</b>	35.00
<b>Days:</b>	1
<b>Load (lbs/day):</b>	257.85

Load Class	Code	Points
< 100 lbs/day	1	0
< 1000 lbs/day	2	5
<5000 lbs/day	3	15
>5000 lbs/day	4	20

**Factor 3 Score: 5**

**FACTOR 4 Public Health Impact**

Is a public drinking water intake located within 50 miles downstream of discharge?

Answer	Points
No	0
Yes	See below

If yes, determine the *human health* toxicity potential:

SICCode	Permit Has Prep Plant	Human Health Toxicity Group	Points
1221		5	5
1221	X	6	10
1222		5	5
1222	X	6	10

**Factor 4 Score: 0**

**FACTOR 5 Water Quality Factors**

A) Is (or will) one or more of the effluent discharge limits based on water quality factors of the receiving stream (rather than technology-based federal effluent guidelines, or technology-based state effluent guidelines), or has a waste load allocation been assigned to the discharge?

Answer	Code	Points
Yes	1	10
No	2	0

**Factor 5a Score: 10**

B) Is the receiving water in compliance with applicable water quality standards for pollutants that are water quality limited in the permit?

Answer	Code	Points
Yes	1	0
No	2	5

**Factor 5b Score: 0**

C) Does the effluent discharged from this facility exhibit the reasonable potential to violate water quality standards due to whole effluent toxicity?

Answer	Code	Points
Yes	1	10
No	2	0

**Factor 5c Score: 0**

**Factor 5 Total Score: 10**

**Factor 6 Proximity to Near Coastal Waters**

Is the permit within 50 miles of near coastal waters?

Answer	Points
Yes	5
No	0

**Factor 6 Score: 0**

**Worksheet Score (factors 1 through 6): 40**

## Appendix D (Coal Facility Discretionary Major Weighting Factor Guideline)

### 1) Annual Coal Mined or Processed

Tons/year	Points
≥ 1,500,000	4
≥ 500,000 and < 1,500,00	2
< 500,000	0

Factor D1 Score: 4

### 2) Coal Origin

Is the coal mined from an acidic seam?

Answer	Points
Yes	5
No	0

Factor D2 Score: 5

### 3) Average Discharge Rate

Discharge	Points
≥ 1,500 GPM	5
< 1,500 and ≥ 500 GPM	3
< 500 GPM	1

Factor D3 Score: 3

### 4) Receiving Stream

Classification	Points
Trout (cold-water fishery)	5
Other high quality	3
Other	0

Factor D4 Score: 0

### 5) Average Discharge to TMDL Watershed(s)

TMDL Discharge	Points
≥ 500 GPM	10
< 500 GPM	0

Factor D5 Score: 10

Appendix D Score: 22

### Score Summary

If the worksheet score for factors 1 through 6 is less than 80 and the Appendix D score is greater or equal to 15, add 500 points to worksheet score.

**Final Worksheet Score : 540**

**Major or Minor Source: Major Source**

**Appendix VI: TMDL Wasteload Change Estimations**

Black Creek MN Estimated Wasteload Changes								
Est Flow = 0.30, Est Conc. = 2.00								
Outfall	Watershed Acre Change	$\Delta WL_{\text{Watershed}}$ (kg/year)	Disturbed Acres	Remining Acres	% NonRemine	$\Delta \text{Flow}_{\text{Other}}$ (kg/year)	$\Delta WL_{\text{Other}}$ (kg/year)	$\Delta WL_{\text{Total}}$ (kg/year)
T	38.80	46.32	27.90	0.00	100.00%	0.00	0.00	46.32
<b>Total</b>	38.80	46.32	333.40	0.00	100.00%	0.00	0.00	46.32

Powell River TSS Estimated Wasteload Changes								
Est Flow = 0.50, Est Conc. = 35.00								
Outfall	Watershed Acre Change	$\Delta WL_{\text{Watershed}}$ (kg/year)	Disturbed Acres	Remining Acres	% NonRemine	$\Delta \text{Flow}_{\text{Other}}$ (kg/year)	$\Delta WL_{\text{Other}}$ (kg/year)	$\Delta WL_{\text{Total}}$ (kg/year)
T	38.80	1,350.95	27.90	0.00	100.00%	0.00	0.00	1,350.95
<b>Total</b>	38.80	1,350.95	367.10	0.00	100.00%	0.00	0.00	1,350.95

**Appendix VII: TMDL Offset Balances**

There is no associated offset information for this permit/application.

**Revision Application**

**Application No:** 1011618  
**CSMO No:** 1601576

**Approval Date:** 11/18/2024  
**NPDES No:** 0081576

**I. APPLICANT INFORMATION**

**Name:** RED RIVER COAL COMPANY, INC.  
**Address:** P. O. BOX 668

**Facility:** BLACK CREEK SURFACE MINE  
**Location:** 0.3 MILES FROM  
BLACKWOOD/JOSEPHINE/LAURE  
L GROVE

**City:** NORTON

**State Plane - North:** 3531902.4580

**State:** VA

**Zip:** 24273

**State Plane - East:** 10261902.1120

**Telephone:** (276)679-1400

**Total Acres:** 1331.78

**Operator:** JAMES M. THOMAS

**Inspector:** CLEVINGER, JOHN

Types of Mining
Undergrd. - R P
Surf-Auger/HW Miner
Surface-Contour
Surface - Area
Surf-Steep Slop

County
WISE

Quadrangle
NORTON

Receiving Stream	Code	Watershed	Wtr #	Basin
BENTLEY HOLLOW	1118	POWELL-POWELL RIVER DORCHESTER	PO17	TENNESSEE
BLACK CREEK	130	POWELL-POWELL RIVER DORCHESTER	PO17	TENNESSEE
BEAR BRANCH (sc.3 NORTON)	135	POWELL-POWELL RIVER DORCHESTER	PO17	TENNESSEE
POWELL RIVER	2	POWELL RIVER	PO	TENNESSEE

**II. CONTRACT LABORATORY SERVICES**

**Laboratory Services will be performed by:**

**Laboratory Name:** ENV. MONITORING, INC.(EMI)

**Address:** 5730 Industrial Park Rd.

**City:** NORTON

**State:** VA

**Zip:** 24273

**Telephone:** (276)679-6544

**Comments:** [2/11/2025, dmmeexp]APPNO 1011619 PLANS REVISION  
NPDES ADDED: T (0012749)  
9/11/2024 NPDES OUTFALL C (MPID 0002312)  
UPDATED TO RECLAMATION AREA EFFLUENT LIMITATIONS  
BY INSPECTION JKC0006031 - 0261682 EFFECTIVE DATE 8/6/2024  
(Drainage Area Vegetated). dmmeexp.7/31/2024 NPDES OUTFALL D  
(MPID 0002313) DELETED BY INSPECTION JKC0005951 - 0261254  
EFFECTIVE DATE 6/17/2024 (Sediment Structures Removed). dmmejkw.4/2/2024 NPDES OUTFALL O  
(MPID 0003836) DELETED BY INSPECTION JKC0005822 - 0260240  
EFFECTIVE DATE 2/27/2024 (Remove Never Constructed). dmmejkw.4/2/2024 NPDES OUTFALL B  
(MPID 0002311) DELETED BY INSPECTION JKC0005822 - 0260240  
EFFECTIVE DATE 2/27/2024 (Sediment Structures Removed). dmmejkw.12/7/2023 NPDES OUTFALL 13-  
1  
(MPID 1770001) DELETED BY INSPECTION JKC0005638 - 0258850  
EFFECTIVE DATE 9/28/2023 (Sediment Structures Removed). dmmejkw.1/11/2023 NPDES OUTFALL R  
WEIR

(MPID 0004086) DELETED BY INSPECTION JKC0005176 - 0255920  
EFFECTIVE DATE 11/1/2022 (Sediment Structures Removed). dmmsesrw.12/1/2022 NPDES OUTFALL Q WEIR

(MPID 0004088) DELETED BY INSPECTION JKC0005176 - 0255920  
EFFECTIVE DATE 11/1/2022 (Sediment Structures Removed). dmmsesrw.12/1/2022 NPDES OUTFALL Q

(MPID 0004087) DELETED BY INSPECTION JKC0005176 - 0255920  
EFFECTIVE DATE 11/1/2022 (Sediment Structures Removed). dmmsesrw.12/1/2022 NPDES OUTFALL J

(MPID 0004090) DELETED BY INSPECTION JKC0005129 - 0255639  
EFFECTIVE DATE 9/29/2022 (Sediment Structures Removed). dmmsesrw.5/25/2022 NPDES OUTFALL IE

(MPID 0002314) DELETED BY INSPECTION JKC0004950 - 0254517  
EFFECTIVE DATE 6/1/2022 (Other - specified in comments). dmmseslh. [11/16/2021, dmmsesmf]APPNO 1011092 ACRES AMENDMENT

GROUNDWATER ADDED: P-11 (0012106) NPDES CHANGED: IE (0002314) PERMIT RENEWAL APPLICATION 1011100 AND ACREAGE AMENDMENT APPLICATION 1011092 WERE IN REVIEW AT THE SAME TIME, THEREFORE THE RENEWAL NPDES PERMIT HAS BEEN UPDATED TO INCLUDE CHANGES MADE IN THE ACREAGE AMENDMENT. THIS FACTSHEET REFLECTS CHANGES MADE IN BOTH APPLICATIONS. CORRECTING COORDINATE LOCATIONS FOR NPDES OUTFALLS B, D, IK AND S, AND GROUNDWATER LOCATION UD-B. SITE HAS POLLUTION ABATEMENT DISCHARGES DUE TO PRE-SMCRA MINING OPERATIONS. LOCATED IN POWELL AND BLACK CREEK WATERSHEDS. THE BLACK CREEK PORTION OF THIS PERMIT HAS BEEN BACKFILLED, GRADED AND HYDRO-SEEDED. MINING ON MUCH OF THE REMAINING PERMIT HAS BEEN COMPLETED, AND THE AREA HAS BEEN VEGETATED WITH TREES PLANTED WITH PHASE II BOND REDUCTION. CURRENTLY MINING IS CONTINUING IN THE SOUTHERN PART OF THE PERMIT.

9/28/2021 NPDES OUTFALL IK

(MPID 0002675) DELETED BY INSPECTION JKC0004615 - 0252401  
EFFECTIVE DATE 9/28/2021 (Sediment Structures Removed). dmmseslh.9/28/2021 NPDES OUTFALL 11-1

(MPID 1784113) DELETED BY INSPECTION JKC0004615 - 0252401  
EFFECTIVE DATE 9/28/2021 (Sediment Structures Removed). dmmseslh.9/28/2021 NPDES OUTFALL IF

(MPID 0002315) DELETED BY INSPECTION JKC0004615 - 0252401  
EFFECTIVE DATE 9/28/2021 (Sediment Structures Removed). dmmseslh.9/28/2021 NPDES OUTFALL N

(MPID 0003503) DELETED BY INSPECTION JKC0004615 - 0252401  
EFFECTIVE DATE 9/28/2021 (Sediment Structures Removed). dmmseslh. [6/23/2020, dmmeaxh]RA APPNO 1010914 APPROVED 6/23/20 TO AMEND 5.00 ACRES FOR ADDITIONAL MINING AREA, TO DELETE 5.00 ACRES OF UNDISTURBED MINING AREA FOR A ZERO NET GAIN IN MINING AREA, AND TO REVISE THE INCREMENTAL BONDING PLAN/MAP.

REMINING PERMIT

02/02/2017: TJ APPNO 1009845-3 APPROVED 01/27/17 AS CSMO/ NPDES PERMIT RENEWAL 1601576/0081576. RED RIVER COAL COMPANY, INC. - BLACK CREEK SURFACE MINE. EXTENDS THE TEMPORARY CESSATION PERIOD ON 42.80 ACRES TO 03/27/19. DELETE CHEMICAL ONLY MONITORING POINTS D & G (MPID 0007942 & 0007943). UPDATE DETAILS ON NPDES OUTFALLS B, IE, IF, H, MD-3, IK, R WEIR, Q WEIR, & 11-1 (MPID 0002311, 0002314, 0002315, 0002316, 0002348, 0002675, 0004086, 0004088, & 1784113. AXH

\*\* LAB: ENV. MONITORING, INC. (EMI)(1) SIGNING DMRs: JAMES M. THOMAS & EDDIE CLAPP \*\*

06/18/14: RP APPNO 1009059-3/1601576 APPROVED 02/03/2014 TO DELETE IN-STREAM FLOW ONLY MONITORING POINTS F0-1, F0-3, F0-4, F0-5, F0-6, AND F0-7 (MPID NO'S 0004780, 0005391, 0005853, 0005854, 0006539, 0006540) AND ALLUVIAL WELLS MONITORING POINTS AW-1 AND AW-2 (MPID NO'S 0005851, 0005852). PRB/NC

03/06/13: PLAN MOD DLH0008797/1601576 DATED 02/28/13 TO DELETE NPDES MONITORING POINT R, MPID NO 0004085, POND R, HAS BEEN REMOVED AND THE AREA RECLAIMED BY INSPECTION REPORT DATED 9/29/11. JKW/MH

03/06/2013: TJ APPNO 1007615-7 APPROVED 01/30/13 AS CSMO/ NPDES PERMIT RENEWAL 1601576/0081576, RED RIVER COAL COMPANY, INC. - BLACK CREEK SURFACE MINE. ADD 7 SURFACE WATER INSTREAM MONITORING POINTS: PR1, PR2, BC1, BC4, D, G

& BC3 (MPID NO'S 0007938 THRU 0007944), BIOLOGICAL-CHEMICAL SAMPLING REQUIRED. JKW/MMH  
11/05/2012: RP APPNO 1008284-2/1601576 APPROVED 08/28/12 TO RELOCATE EXISTING POND H, MPID NO 0002316, AND CONSTRUCT IT LARGER TO CONTROL THE EXISTING DRAINAGE AREA AND TO REMOVE EXISTING POND H1. JKW/MMH  
01/24/2011: PLAN MOD DLH0006578/1601576 APPROVED 01/13/09 TO DELETE GROUNDWATER POINT GWMP-1, MPID 0004736. PRB/MMH  
10/27/09: RP APPNO 1006343-1/1601576 APPROVED 10/20/09 TO DELETE GROUNDWATER MONITORING POINTS MD-PH1, MPID 0005435, AND W-MH1, MPID 0005436. PRB/MMH  
07/21/09: RP APPNO 1005974-4/1601576 APPROVED 07/14/09 TO UPDATE THE POINT DETAILS INFORMATION FOR OUTFALL 11-1, MPID NO. 1784113. JKW/MMH  
7/14/2009: PM IRN DLH0006352/1601576 DATED 08/06/08 TO REMOVE POND 10, OUTFALL 11-10, MPID 1770033. PRB/CFS  
04/29/09: MT APPNO 1005780-4/1601576 APPROVED 04/28/09 AS MID-TERM REVIEW. UPDATE DETAIL INFORMATION FOR SEVERAL GROUNDWATER POINTS (GWMP-1, MD-3, MD-7 THRU MD-12, P-1, P-2, P-3, UD-B, UD-C, UD-D & VT-UD1) & NPDES OUTFALL 11-1. PRB/MH  
02/19/2009: UPDATE RECORDS: TAKE OFF DELETED DATE OF 8/22/06 FOR NPDES OUTFALL A. POND A WAS DELETED NOVEMBER 2005 AND NOT POND A1. OUTFALL A MOVED TO IN SERIES STRUCTURE POND A1, MONITORING OF OUTFALL A (MPID 0002310) WILL RESUME AT THIS ASSOCIATED STRUCTURE NEXT MONTH. JKW  
01/13/2009: SEE 01/24/11 COMMENTS ON PLAN MOD DLH0006578 TO DELETE GW SITE GWMP-1. MMH  
12/21/06: TJ APPNO 1003634-3 APPROVED 12/19/06 AS CSMO/ NPDES PERMIT RENEWAL 1601576/0081576, RED RIVER COAL COMPANY, INC. - BLACK CREEK SURFACE MINE. ALL 24 NPDES COORDINATES HAVE BEEN CHANGED INCLUDING OUTFALL A (DELETED 08-22-06). CSW/MMH  
LAB: ENVIRONMENTAL MONITORING, INC. (1) POB 1190, NORTON VA 24273, 276.679.6544, SIGNING DMRS: JAMES M. THOMAS AND EDDIE CLAPP  
10/31/06: RP APPNO 103937-1/1601576 APPROVED TO DELETE GROUNDWATER MONITORING POINTS AW-3 (MPID #0006537) AND AW-4 (MPID #0006538).  
10/17/06: RP APPNO 1003909/1201803, MINE DEWATERING WELL NO. 2 WILL BE CONSTRUCTED ON P.N. 1201803 TO DEWATER THE AMERICAN ENERGY DEEP MINE ASSOCIATED WITH THIS PERMIT (P.N. 1601576). PRB/MMH  
10/12/2006: RP APPNO 1003535-2/1601576 APPROVED 10/12/06 TO ADD GW MONITORING LOCATIONS AW-3 (UP ROCKY, MPID 0006537) AND AW-4 (DOWN ROCKY, MPID 0006538). ADDING IN-STREAM MONITORING LOCATIONS FO-6 (UPSTREAM ROCKY FORK, MPID 0006539) AND FO-7 (DOWNSTREAM POWELL RIVER, MPID 0006540), FLOW-ONLY MONITORING. MFS/MMH  
08/22/2006: PLAN MODIFICATION BY IRN RWH0004412/1601576 APPROVED 08/22/06 TO DELETE NPDES OUTFALL A, MPID #0002310, POND A REMOVED NOVEMBER 2005. MMH  
03/04/05: RP APPNO 1001955-3/1601576 APPROVED 02/28/05. THE PMU BOUNDARY OF THE NORTON SEAM DEEP MINE IS EXTENDED IN THE EASTERN AND SOUTHEASTERN PARTS OF THE EXISTING PMU. APPROXIMATELY 682 ACRES WILL BE ADDED TO THE PMU. ADD GROUNDWATER POINTS AW-1 (MPID 0005851) AND AW-2 (0005852). ADD FLOW-ONLY INSTREAM POINTS FO-4 (0005853) AND FO-5 (0005854). PRB/MMH  
01/19/2005: MID-TERM REVIEW APPLICATION 1001991-5/1601576 APPROVED 12/16/04 TO DELETE NPDES OUTFALL 11-2 (MPID 1784114) AS POND 2 HAS BEEN MINED THROUGH. MFS  
03/23/04: RA APPNO 1001458-5/1601576 APPROVED 03/16/04 TO



AMEND 0.64 ACRE IN ORDER TO ADD WELLS DH-1, MD-PH-1, W-MH1, AND RELATED ACCESS ROADS FOR DISCHARGING PUMPED WATER FROM THE AMERICAN ENERGY DEEP MINE IN THE NORTON SEAM AND MONITORING THE WATER LEVEL IN THE OLD DORCHESTER MINE WORKS. IN ADDITION TO THE 0.64 ACRE AMENDMENT, AN ADDITION OF 5.70 ACRES IS BEING MADE AS A BOUNDARY CORRECTION BASED ON UP-DATED BASE MAPPING. ADD GROUNDWATER POINTS MD-PH1 (MPID #0005435-SAMPLING ON THE SURFACE AT THE PUMP SITE, PRIOR TO DISCHARGE INTO THE OLD DORCHESTER MINE WORKS, NO QUANTITY MEASUREMENTS) AND W-MH1 (MPID #0005436-WELL USED TO DETERMINE WATER LEVEL ONLY IN THE DORCHESTER MINE). PRB/MMH 01/20/2004: RP APPNO 1001517-3/1601576 TO ADD GROUNDWATER POINT GWMP-1 (MPID #0004736), WHICH WILL BE SHARED WITH PN 1201803 (RRCCI). ADD INSTREAM POINT FO-3 (0005391) AS A FLOW ONLY MONITORING POINT. ADD APPROXIMATELY 27 ACRES TO THE UNDERGROUND MINING LIMITS (PMU) IN THE NORTON COAL SEAM. 05/16/2003: RP APPNO 1001059-2/1601576 TO ADD NPDES OUTFALLS (MPID #0005150) TO THIS PERMIT. CSW/MMH 08/13/02: RP APPNO 1000341-3/1601576 APPROVED 08/01/02 FOR ADDITIONAL PMU 590 ACRES ADDED. ADDING FLOW ONLY POINTS F-01 (0004780) AND F-02 (0004740) TO BE MONITORED 1 YEAR WHILE OPERATION CROSSES UNDER POWELL RIVER. ADDING INSTREAM POINTS ISMP-5 (0004778), ISMP-6 (0004741), ISMP-7 (0004779), UPDATE RECEIVING STREAM AND FACILITY LOCATION FOR INSTREAM MONITORING POINT VT-UD1 (0002376). MFS/MMH 06/17/2002: RP APPNO 1000132-2/1601576 APPROVED TO ADD NPDES POND Q1 AND RELOCATE OUTFALLS Q (0004087) AND Q WEIR (0004088) TO POND Q1 (SAME COORDINATES). PRB/MMH 10/11/01: TJ APPNO 5601909 APPROVED 10/11/01 AS CSMO/NPDES PERMIT RENEWAL, RED RIVER COAL COMPANY, INC.-BLACK CREEK SURFACE MINE. CORRECT NAMES OF NPDES OUTFALLS TE & TF TO IE AND IF (0002314 & 0002315) TO CORRESPOND TO ORIGINAL APPLICATION. INSERT ADDED NPDES DATES FOR MD-1, MD-2, MD-3, AND MD-4 AS ORIGINAL PERMIT ISSUANCE (09/27/96); INSERT DELETED DATE OF 03/09/01 FOR NPDES OUTFALLS MD-1, MD-2, AND MD-4 (PER 9608491). PRB/MMH 08/01/01: RP APPNO 9608623/1601576 TO ADD GW SITE UD-BF1 (ADDING BENCH FILL #1 PER NOV). CSW/MMH 04/19/01: RP APPNO 9608526/1601576 APPROVED 04/17/01 TO ADD NPDES SITE J (MPID #0004090), 21-13 LIMIT FOR POND J. CSW/MH 03/12/2001: RP APPNO 9608491/1601576 APPROVED 03/09/01 TO ADD NPDES SITES Q, Q WEIR, R, AND R WEIR; DELETE GW SITES MD-1, MD-2 & MD-4; & DELETE IN-STREAM SITES MD-1, MD-2 & MD-4. MD-4. CSW/MMH 09/15/00: RP APPNO 9608251 APPROVED 08/14/00 TO ADD POND P (BENCH BASIN) IN SERIES WITH EXISTING POND E (OUTFALL TE). NO MONITORING CHANGES. MMH 08/14/00: RA APPNO 9608206/1601576 TO ADD NPDES SITE O (POND O) 21-09. CSW/MMH 01/11/2000: RP APPNO 9607964/1601576 APPROVED 12/15/99 TO ADD NPDES OUT FALL N, POND N (MPID #0003503, LIMIT 21-13). 08/12/99: RP APPNO 9607842/1601576 APPROVED 08/10/99 TO ADD POND M (OUTFALL M) AND INSTREAM SITE R-3 (SHARING WITH PN 1101096, MPID #1720020). CSW/MMH LAB: ENVIRONMENTAL MONITORING, INC. (1) POB 1477, COEBURN, VA 24230, 540-395-3661, SIGNING DMRS: DANNY SHORTT AND EDDIE CLAPP. 04/01/99: PER CSW COLLECT ONE COMPLETE ANALYSIS PER MONTH FOR MD-1, MD-2, MD-3, MD-4, MD-5, MD-6 AND MD-9. ALSO DELETE THE ABOVE OUTFALLS FROM THE INSTREAM MONITORING PLAN. 02/26/99: LETTER TO DANNY SHORT WITH EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS FOR RE-MINING SOURCE GWEIR

(21-31-R) WHICH WAS LEFT OFF LETTER/FORMS ON 2/19/99. MMH  
 02/19/99: PER ORIGINAL PLANS APPROVED 01/28/98 TO START  
 MONITORING NPDES SITE G (21-30-R) MD-5 & MD-6; ADD NPDES  
 SITE GWEIR (21-31-R); DELETE GW & IS SITES MD-5 & MD-6.  
 01/20/99: RP APPNO 9607655/1601576 APPROVED 12/29/98: NOTE  
 TO FILES: CLAYTON WILES INDICATED HE WOULD APPROVE OF THE  
 RELOCATION AFTER DISCUSSIONS WITH COMPANY REPRESENTATIVES.  
 I SEE NO PROBLEMS WITH RELOCATING OUTFALL 13-1 APPROXIMA-  
 TELY 200 FEET DOWNSTREAM. NO OTHER CHANGES ARE PROPOSED.  
 JOEY O' QUINN.MMH  
 09/18/97: RP APPNO 9607118/1601576 APPROVED 9/9/97 TO ADD  
 NPDES SITE IK (I POND K), LIMIT 21-13. CSW/MMH  
 06/30/1997: RP APPNO 9607028/1601576 APPROVED 6/17/97 TO  
 COMPLY T.O.I. CONCERNING STREAM CHANNEL RELOCATION AND  
 HABITAT RESTORATION, START MONITORING NPDES SITES 11-1,  
 11-2, 11-10, 13-1, H & I. MMH  
 09/27/1996: NJ APPNO 0602131 ISSUED AS CSMO/NPES PERMIT  
 1601576, RED RIVER COAL COMPANY, INC.-BLACK CREEK SURFACE  
 MINE. RELINQUISH CSMO #1201117, BETTY B. COAL CO., INC.  
 CONDITIONAL ISSUANCE UPON SATISFYING EPA'S GENERAL  
 OBJECTION FOR NPDES SITES H, I, 11-1, 11-2, 11-10 & 13-1;  
 ALSO POLLUTION ABATEMENT SITES WON'T BECOME ACTIVE FOR AT  
 LEAST 1 YEAR (MD-1, MD-2, MD-3 & MD-4). MMH  
 LAB: CERTIFIED MINE SERVICES, INC. (2) 6700 HURRICANE ROAD,  
 WISE, VA 24293, 540-328-8683, SIGNING DMRS: EDDIE CLAPP AND  
 DANNY SHORTT.

III. NPDES DISCHARGE SITES

MPID	Outfall Facility	State Plane N State Plane E	Stream Name	Quad Section	Added Deleted	Limit	Stat
0002310	A POND A1	3525043.748900 10262883.429600	2 POWELL RIVER	NORTON 5	9/27/1996 5/1/2024	21-13	ND
0002311	B POND B	3523687.120000 10261529.260000	2 POWELL RIVER	NORTON 5	9/27/1996 2/27/2024	30-19	ND
0002312	C POND C	3524152.710495 10258981.590867	2 POWELL RIVER	NORTON 5	9/27/1996	21-19	ND
0002313	D POND D	3524879.220000 10258609.170000	2 POWELL RIVER	NORTON 5	9/27/1996 6/17/2024	30-13	A
0002314	IE TMP POND E	3527671.486800 10259408.464000	130 BLACK CREEK	NORTON 5	9/27/1996	30-13	A
0002315	IF TMP POND F	3526483.013100 10258938.763600	130 BLACK CREEK	NORTON 5	9/27/1996 9/28/2021	30-19	ND
0002316	H POND H	3540740.557000 10269619.735400	2 POWELL RIVER	NORTON 3	6/17/1997	21-13	ND
0002317	I POND I	3541796.652300 10266100.529100	2 POWELL RIVER	NORTON 3	6/17/1997 5/1/2024	21-13	ND
0002345	G MD-5 & 6	3534787.661000 10262516.751300	130 BLACK CREEK	NORTON 5	1/28/1998 5/1/2024	30-30	A
0002346	MD-1 ALT EFFL	3537779.155736 10262381.397216	130 BLACK CREEK	NORTON 2	9/27/1996 3/9/2001	21-13	NC
0002347	MD-2 ALT EFFL	3537010.553793 10262294.395753	130 BLACK CREEK	NORTON 2	9/27/1996 3/9/2001	21-13	NC
0002348	MD-3 ALT EFFL	3536304.668200 10262062.893000	130 BLACK CREEK	NORTON 2	9/27/1996 5/1/2024	30-13	NC

MPID	Outfall Facility	State Plane N State Plane E	Stream Name	Quad Section	Added Deleted	Limit	Stat
0002349	MD-4 ALT EFFL	3536179.386116 10262154.831451	130 BLACK CREEK	NORTON 2	9/27/1996 3/9/2001	21-13	NC
0002675	IK I POND K	3524881.020000 10258590.570000	130 BLACK CREEK	NORTON 5	9/9/1997 9/28/2021	30-19	ND
0003201	G WEIR REMG WEIR	3534787.660989 10262516.751341	130 BLACK CREEK	NORTON 5	1/28/1998	30-31	A
0003369	M POND M	3527382.297399 10264464.260141	1118 BENTLEY HOLLOW	NORTON 5	8/10/1999	30-19	ND
0003503	N POND N	3528339.969700 10259525.068665	130 BLACK CREEK	NORTON 5	12/15/1999 9/28/2021	30-13	ND
0003836	O POND O	3538838.464000 10268674.907700	135 BEAR BRANCH (sc.3 NORTON)	NORTON 3	8/14/2000 2/27/2024	21-09	NC
0004085	R POND R	3538005.651166 10262545.545837	130 BLACK CREEK	NORTON 2	3/9/2001 9/29/2011	21-30	A
0004086	R WEIR WEIR BELOW	3538005.651200 10262545.545000	130 BLACK CREEK	NORTON 2	3/9/2001 11/1/2022	30-31	A
0004087	Q PDS Q&Q1	3535475.301890 10262230.150874	130 BLACK CREEK	NORTON 2	3/9/2001 11/1/2022	30-30	A
0004088	Q WEIR WEIR BELOW	3535475.301900 10262230.150900	130 BLACK CREEK	NORTON 2	3/9/2001 11/1/2022	30-31	A
0004090	J POND J	3538880.581234 10262528.899431	130 BLACK CREEK	NORTON 5	4/17/2001 9/29/2022	30-13	ND
0005150	S POND S	3539408.340000 10262012.470000	130 BLACK CREEK	NORTON	5/16/2003	30-13	ND
0012749	T Pond T	3531126.200000 10262185.720000	130 BLACK CREEK	NORTON	11/18/2024		
0012857	T Pond T	3531126.200000 10262185.720000		NORTON	11/18/2024	30-13	A
1770001	13-1 POND 1	3531121.832456 10260485.496734	130 BLACK CREEK	NORTON 5	6/17/1997 9/28/2023	30-13	ND
1770033	11-10 POND 10	3527629.082891 10259254.306513	130 BLACK CREEK	NORTON 5	6/17/1997 8/6/2008	21-13	ND
1784113	11-1 POND 11-1	3527199.706200 10259441.946800	130 BLACK CREEK	NORTON 5	6/17/1997 9/28/2021	30-19	ND
1784114	11-2 POND 2	3526483.013054 10258938.763620	130 BLACK CREEK	NORTON 5	6/17/1997 12/16/2004	21-13	ND

## IV. GROUNDWATER MONITORING SITES

MPID	Outfall Facility	State Plane N State Plane E	Elevation Type	Quad Section	Added Deleted	Stat
0002350	UD-A	3524749.167100 10263525.259600	2020.00 UNDERDRAIN	NORTON 5	9/27/1996 5/1/2024	A
0002351	UD-B Fill B	3527688.760000 10259897.260000	2050.00 UNDERDRAIN	NORTON 5	9/27/1996	A
0002352	UD-C Fill C	3532169.957600 10262543.452900	2115.00 UNDERDRAIN	NORTON 5	9/27/1996 5/1/2024	NC
0002353	UD-D Fill D	3533732.159300 10264263.525800	2160.00 UNDERDRAIN	NORTON 5	9/27/1996 5/1/2024	NC

MPID	Outfall Facility	State Plane N State Plane E	Elevation Type	Quad Section	Added Deleted	Stat
0002354	P-1 north end	3540356.267700 10269555.812000	2365.00 PIEZOMETER	NORTON 3	9/27/1996 5/1/2024	A
0002355	P-2 south entr	3524827.611800 10258430.924200	1900.00 PIEZOMETER	NORTON 5	9/27/1996 5/1/2024	A
0002356	P-3 bkcreekent	3533176.694500 10262744.955200	2110.00 PIEZOMETER	NORTON 5	9/27/1996 5/1/2024	NC
0002357	MD-1	3537790.296744 10262383.959744	2195.00 MINE DISCH	NORTON 2	9/27/1996 3/9/2001	A
0002358	MD-2	3537020.116603 10262295.958274	2210.00 MINE DISCH	NORTON 2	9/27/1996 3/9/2001	A
0002359	MD-3 dorchester	3536304.668200 10262062.893700	2280.00 MINE DISCH	NORTON 2	9/27/1996 5/1/2024	A
0002360	MD-4	3536184.386351 10262158.206474	2190.00 MINE DISCH	NORTON 2	9/27/1996 3/9/2001	A
0002361	MD-5	3535149.555255 10262510.894304	2160.00 MINE DISCH	NORTON 5	9/27/1996 1/28/1998	A
0002362	MD-6	3534829.127354 10262611.831860	2130.00 MINE DISCH	NORTON 5	9/27/1996 1/28/1998	A
0002363	MD-7 norton sm	3532304.970200 10262858.329600	2170.00 MINE DISCH	NORTON 5	9/27/1996 5/1/2024	A
0002364	MD-8 norton sm	3531859.490300 10261785.136400	2122.00 MINE DISCH	NORTON 5	9/27/1996 5/1/2024	A
0002365	MD-9 norton sm	3531579.575100 10261742.073300	2120.00 MINE DISCH	NORTON 5	9/27/1996 5/1/2024	A
0002366	MD-10 norton sm	3532580.852400 10262838.829900	2180.00 MINE DISCH	NORTON 5	9/27/1996 5/1/2024	A
0002367	MD-11 norton sm	3526576.753600 10259027.929100	2000.00 MINE DISCH	NORTON 5	9/27/1996 5/1/2024	A
0002368	MD-12 norton sm	3526753.948700 10259127.492300	2015.00 MINE DISCH	NORTON 5	9/27/1996 5/1/2024	A
0002369	VT-UD1 dorchester	3540348.271300 10262828.090400	2335.00 UNDERDRAIN	NORTON 2	9/27/1996 5/1/2024	A
0004303	UD-BF1 BENCHFILL1	3535121.856700 10262742.792900	2160.00 UNDERDRAIN	NORTON 5	8/1/2001 5/1/2024	A
0004736	GWMP-1 upstpowell	3540493.087900 10274932.902000	2115.00 WELL	NORTON	1/12/2004 1/13/2009	A
0005435	MD-PH1 NORTON PMP	3539939.991300 10272237.887400	2215.00 MINE DISCH	NORTON	3/16/2004 10/20/2009	A
0005436	W-MH1 DORCHESTER	3540377.015700 10272623.890100	2264.00 WELL	NORTON	3/16/2004 10/20/2009	A
0005851	AW-1 UP GUEST	3543261.288900 10278821.927100	2125.00 WELL	NORTON	2/28/2005 2/3/2014	A
0005852	AW-2 DOWN GUEST	3542615.276900 10279079.927100	2125.00 WELL	NORTON	2/28/2005 2/3/2014	A
0006537	AW-3 UP ROCKY		WELL	WISE	10/12/2006 10/31/2006	NC
0006538	AW-4 DOWN ROCKY		WELL	WISE	10/12/2006 10/31/2006	NC

MPID	Outfall Facility	State Plane N State Plane E	Elevation Type	Quad Section	Added Deleted	Stat
0012106	P-11 amend poit	3530921.420000 10263538.880000	2450.00 PIEZOMETER	NORTON	11/9/2021	A

#### V. IN-STREAM MONITORING SITES

MPID Mp Is No	Outfall Facility	State Plane N State Plane E	Stream Name	Quad Section	Added Deleted	Stat
0002357	MD-1	3537790.296744 10262383.959744	130 BLACK CREEK	NORTON 2	9/27/1996 4/1/1999	A
0002358	MD-2	3537020.116603 10262295.958274		NORTON 2	9/27/1996 4/1/1999	A
0002359	MD-3 dorchester	3536304.668200 10262062.893700		NORTON 2	9/27/1996 4/1/1999	A
0002360	MD-4	3536184.386351 10262158.206474		NORTON 2	9/27/1996 4/1/1999	A
0002361	MD-5	3535149.555255 10262510.894304		NORTON 5	9/27/1996 1/28/1998	A
0002362	MD-6	3534829.127354 10262611.831860		NORTON 5	9/27/1996 1/28/1998	A
0002365	MD-9 norton sm	3531579.575100 10261742.073300		NORTON 5	9/27/1996 4/1/1999	A
0002370	ISMP-1 POWELL RIV	3524732.210000 10258011.480000	2 POWELL RIVER	NORTON 5	9/27/1996	A
0002371	ISMP-2 UPSTREAM	3524215.149641 10264024.073545	2 POWELL RIVER	NORTON 5	9/27/1996	A
0002372	ISMP-3 UPSTREAM	3540672.880672 10270419.004378	130 BLACK CREEK	NORTON 3	9/27/1996	A
0002373	ISMP-4 DOWNSTREAM	3525658.222259 10258793.239421	130 BLACK CREEK	NORTON 5	9/27/1996	A
0002376	VT-UD1 UPSTREAM	3540348.271300 10262828.090400	130 BLACK CREEK	NORTON 2	9/27/1996 5/1/2024	A
0004740	BL-1 UPSTREAM	3539980.001000 10272525.888900	2 POWELL RIVER	NORTON	8/1/2002	A
0004741	BL-2 DOWNSTREAM	3539124.079200 10276031.905100	2 POWELL RIVER	NORTON	8/1/2002	A
0004778	ISMP-5 UPSTREAM	3540469.728300 10271811.085100	2 POWELL RIVER	NORTON	8/1/2002 5/1/2024	A
0004779	ISMP-7 DOWNSTREAM	3540729.109300 10275411.904900	2 POWELL RIVER	NORTON	8/1/2002 5/1/2024	A
0004780	FO-1 UPSTREAM	3540469.728300 10271811.085100	2 POWELL RIVER	NORTON	8/1/2002 2/3/2014	A
0005391	FO-3 FLOW ONLY	3539124.079200 10276031.905100	2 POWELL RIVER	NORTON	1/12/2004 2/3/2014	A
0005853	FO-4 UPSTREAM	3543469.075100 10278157.754000	145 GUEST RIVER	NORTON	2/28/2005 2/3/2014	A
0005854	FO-5 DOWNSTREAM	3541314.568300 10279462.186600	145 GUEST RIVER	NORTON	2/28/2005 2/3/2014	A
0006539	FO-6 Upstream	3548625.086500 10282237.462700	230 ROCKY FORK	WISE	10/12/2006 2/3/2014	A

MPID Mp Is No	Outfall Facility	State Plane N State Plane E	Stream Name	Quad Section	Added Deleted	Stat
0006540	FO-7 Downstream	3543502.935900 10281523.877100	2 POWELL RIVER	WISE	10/12/2006 2/3/2014	A
0007938	PR1	3523074.718000 10262232.915000	2 POWELL RIVER	NORTON	1/30/2013	A
0007939	PR2 BIO-CHEMDS	3524556.265000 10257430.198000	2 POWELL RIVER	NORTON	1/30/2013	A
0007940	BC1 BIO-CHEMUS	3526269.315000 10258793.668000	130 BLACK CREEK	NORTON	1/30/2013	A
0007941	BC4 BIO-CHEMDS	3540335.065000 10260339.419000	130 BLACK CREEK	NORTON	1/30/2013	A
0007942	D BIO-CHEMOF	3524801.821800 10258740.370600	2 POWELL RIVER	NORTON	1/30/2013 1/27/2017	A
0007943	G BIO-CHEMOF	3534787.661000 10262516.751300	130 BLACK CREEK	NORTON	1/30/2013 1/27/2017	A
0007944	BC3 midstream	3537500.898000 10262111.320000	130 BLACK CREEK	NORTON	1/30/2013	A
1720020	R-3 BELOW	3524951.416978 10265063.266800	1118 BENTLEY HOLLOW	NORTON 5	8/10/1999	A

#### VI. RAINFALL MONITORING SITES

MPID	Facility	State Plane N	State Plane E	Added	Deleted	Stat
0002374	BLACK CK	3524100.505583	10263428.008208	9/27/1996		A