

A-698  
 14 0.2(+0.4) - Cr Arch  
 13 0.5(+0.3) - Irreg Ox Ptz  
 12 0.3(+0.5) 0.5 - Irreg Ox Ptz 25% Met  
 11 1.6(+1.0) 1.6  
 8 0.4(+1.2) 0.7 - 50% Met  
 5 0.7(+0.3) 0.1 - 50% Met  
 7 0.9(+1.8) 0.1 - 1" My? Br 50°  
 9 8.2(+0.2) 0.1 - Traces  
 17 0.7(+0.7) - 1 Cone Arch - Ble  
 Fa 1 1/2" 30° - 40°

2000  
 Improved 9,000 T 1.2, 3.8 7/26/81  
 11 Est. 0.2, 7.2 Zn  
 12 1.6(+1.0) 1.6  
 13 0.5(+0.3) 0.1 - Irreg Ox Ptz  
 14 0.2(+0.4) 0.1 - Cr Arch

2100  
 Improved 30,200 T 2.3, 0.5 7/26/81  
 5 0.1(+0.3) 0.1  
 7 0.9(+1.8) 0.1  
 9 8.2(+0.2) 0.1  
 17 0.7(+0.7) - 1 Cone Arch - Ble  
 Fa 1 1/2" 30° - 40°

1900  
 2 1/2 Ble Met Cr Arch  
 Fa 1" 54 Ble  
 Fa 3" My 1st Br  
 Few Sgs  
 Small Sgs. MF  
 St Ble  
 Fa 1/2" 45°  
 V Small Sgs. Fa MF  
 Ble Cone Arch?  
 Ra V Small Sgs  
 Few Small MF  
 Hole Thru 3 Level



SERIAL NUMBER	DATE ISSUED	REFERENCE DRAWINGS	REVISIONS	THE NEW JERSEY ZINC COMPANY	DRAWN E.E.F.	DATE 12-11-61
					TRACED	SCALE 1" = 30'
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS DRAWING MUST BE RETURNED TO THE NEW JERSEY ZINC COMPANY.					CHECKED	7GB-5265
					APPROVED	